

## KVM Switch Accessories - NetCommander USB Server Interface Unit (SIU), Virtual Media up to 12Mbps

MODEL NUMBER: **B078-101-USB2**



### Description

The Tripp Lite NetCommander USB Server Interface Unit (SIU) with Virtual Media support connects to the HD15 port and USB ports on a computer/server, and converts them to a single RJ45 connector. Ordinary Cat5e patch cable can then be used to connect the server to the switch ports on a Tripp Lite NetCommander Cat5 IP KVM switch. Supports Virtual Media, with data transfer rates up to 12Mbps.

### Features

- Needed to connect a USB Server to a NetCommander Cat5 IP KVM switch, with virtual media support
- Supports virtual media data transfer rates up to 12Mbps
- Easy to install; no software needed
- No power supply required
- Allows a maximum distance of 100ft from KVM to computer/server via Cat5e cable

### Highlights

- Needed to connect a USB Server to a NetCommander Cat5 IP KVM switch, with virtual media support
- Supports virtual media data transfer rates up to 12Mbps
- Easy to install; no software needed
- No power supply required
- Allows a maximum distance of 100ft from KVM to computer/server via Cat5e cable


### System Requirements



- Server or CPU with a HD15 port and (x2) USB ports
- NetCommander Cat5 IP KVM Switch (**Note: Not compatible with all NetCommander Cat5 IP KVM switches. Contact Tripp Lite Technical Support for information on your model**)
- Cat5e/6 cable; up to 100ft

### Package Includes

- B078-101-USB2 USB Server Interface Unit with Virtual Media Support

## Specifications

OVERVIEW	
Intended Application	Connects a USB computer/server to a NetCommander Cat5 IP KVM Switch
Model Type	Interface Modules
CONNECTIONS	
Connector A	 RJ45 (FEMALE)

Connector B	 HD15 (MALE)
Connector C	 USB A (MALE)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.