

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

5-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch with PoE

MODEL NUMBER: NG5POE







Description

The NG5POE 5-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch adds a Gigabit Ethernet connection with PoE+ capacity to your small office, workgroup or creative workspace.

Especially recommended for security applications to power IP cameras, VoIP phones and other PoE-compatible devices, this energy-efficient switch provides PoE+ compatibility with wireless access points and other devices.

Four ports support up to 26W each with a total PoE budget of 75W. Sharing large bandwidth-intensive files, such as CAD drawings and high-definition videos, at Gigabit speeds improves efficiency and cuts costly downtime. IEEE 802.3x flow control allows smooth transmission.

This unmanaged switch features five twisted-pair RJ45 Gigabit Ethernet ports that support auto-negotiable 10/100/1000 Mbps and auto MDI/MDIX cross-over detection. It's plug-and-play with no configuration required and can be up and running immediately. Easy-to-read LEDs indicate power, connection, activity and PoE status for each port.

The NG5POE supports IEEE 802.3az Energy Efficient Ethernet standards by putting unused ports into a low-power state without interrupting network connections. The detachable five-foot power cord with NEMA 5-15P plug connects to any compatible AC source. The heavy-duty metal housing is designed for desktop installation or mounting into 1U of an EIA-standard 19-inch rack with the included brackets.

Features

Unmanaged Network Switch for Home/Small Offices, Workgroups and Security Applications

- 5 twisted-pair RJ45 Gigabit Ethernet ports
- Auto-negotiable 10/100/1000 Mbps
- Automatic MDI/MDIX cross-over detection
- 10 Gbps switching capacity (2 Gbps per port with full duplex)
- LEDs indicate power, connection, activity and PoE status per port
- Supports 9k jumbo frames, MAC address auto-learning and auto-aging, and 802.3x flow control (full duplex) and back pressure (half duplex)

Highlights

- 5 auto-negotiable 10/100/1000
 Mbps RJ45 ports
- 4 ports support 26W PoE+ each;
 75W total PoE budget
- Supports auto MDI/MDIX
 cross-over function
- 2 Gbps switching capacity per port with full duplex
- Plug-and-play with no configuration required

Package Includes

- NG5POE 5-Port 10/100/1000
 Mbps 1U Rack-Mount/Desktop
 Gigabit Ethernet Unmanaged
 Switch
- Detachable AC power cord with NEMA 5-15P plug, 5 ft.
- (2) Mounting brackets
- (8) Screws
- (4) Rubber feet
- Owner's manual



75W Total PoE+ Budget

- 4 ports support up to 26W PoE+ each
- Each port supplies PoE+ power to connected devices via network cable

Complies with IEEE 802.3az Energy Efficient Ethernet Standards

- Automatically shifts unused ports to low-power state without interrupting network connection
- Also meets IEEE 802.3ab, 802.3i, 802.3u and 802.3 standards

Heavy-Duty Metal Housing

- No-fan design for silent operation
- Detachable 5 ft. AC power cord with NEMA 5-15P plug
- Plug-and-play with no configuration required

Versatile Installation Options

- Includes rubber feet for secure placement on flat desktop surface
- Mounts in 1U of EIA-standard 19 in. rack with included brackets
- Grounding lug included

Specifications

INPUT	
Electrical Consumption	78W maximum power consumption (at 100% switching capacity and 75W continuous POE consumption)
Nominal Input Voltage Description	100-240V AC nominal input
Plug Type	Detachable NEMA 5-15P input cord
Input Cord Length (ft.)	5
Input Cord Length (m)	1.52
Input Frequency	50/60 Hz
USER INTERFACE, ALERTS & CON	ITROLS
LED Indicators	Power LED (Green for Power On); PORTS 1-4 include two LEDs per port (UPPER LED: Green indicates 10/100Mbps link; Amber indicates 1000Mbps link; LEDs flash to indicate port activity / LOWER LED: Green indicates POE is active); PORT 5 includes one LED only (Green indicates 10/100Mbps link; Amber indicates 1000Mbps link; LEDs flash to indicate port activity)
PHYSICAL	
Primary Form Factor	Desktop; Rackmount
Rack Height (U Spaces)	1
Shipping Dimensions (hwd / in.)	3.0 x 9.7 x 17.3
Shipping Dimensions (hwd / cm)	7.62 x 24.64 x 43.94
Shipping Weight (lbs.)	4.7
Shipping Weight (kg)	2.13



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Unit Dimensions (hwd / in.)	1.75 x 11.02 x 7.04
Unit Dimensions (hwd / cm)	4.44 x 27.99 x 17.88
Unit Weight (Ibs.)	3.15
Unit Weight (kg)	1.43
Color	Black
Form Factors Supported	Desktop, Rackmount
ENVIRONMENTAL	
Storage Temperature Range	-40 to 158F (-40 to 70C)
Relative Humidity	10 to 90% (non-condensing)
Operating Elevation (ft.)	Up to 10,000
Operating Temperature	32 to 104F (0 to 40C)
Operating Elevation (m)	Up to 3000
CONNECTIONS	
Network Switch Ports	(5) 10/100/1000 (RJ45)
PoE Supported Ports	4
PoE Capability	30W (802.3at)
PoE Power Budget (Watts)	75
SPECIAL FEATURES	
Grounding Lug	Includes back panel grounding lug
CERTIFICATIONS	
Certifications	Compliant Standards: IEEE 802.3ab (1000BASE-T GIGABIT ETHERNET), IEEE 802.3i (10BASE-T ETHERNET), IEEE 802.3u (100BASE-T ETHERNET), IEEE 802.3x (FULL DUPLEX/FLOW CONTROL), IEEE 802.3 (NWAY AUTO-NEGOTIATION), 802.3az (ENERGY EFFICIENT ETHERNET), 802.3at (POE+)
Approvals	Tested to UL60950-1: 2007 (2ND ED) +A1+A2 R14 (USA), CAN/CSA C22.2 NO. 60950-1-07, 2ND EDITION, 2014-10 (Canada), NOM (Mexico), FCC CLASS B (Emissions)
WARRANTY	
Product Warranty Period (Worldwi	de) 5-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies