

Heavy-Duty Computer Power Cord, 15A, 14 AWG (IEC-320-C14 to IEC-320-C15), Orange, 3 ft.

MODEL NUMBER: P018-003-AOR











Highlights

- Easy-to-identify orange SJT jacket and fully molded orange ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

Package Includes

P018-003-AOR Heavy-Duty
 Computer Power Cord, Orange,
 3 ft.

Description

The P018-003-AOR Heavy-Duty Computer Power Cord features a orange SJT jacket and fully molded orange ends, allowing you to easily identify your connections in a crowded rack or workstation. It features a C14 male connector on one end and a C15 female connector on the other for attaching a high-voltage computer, server or storage drive to a PDU or UPS system.

This three-foot 15A cord supports voltages up to 250V. It's UL-listed and features a flexible SJT jacket and 14 AWG wire for easy routing through tight areas. The P018-003-AOR is recommended for Cisco, HP and other hardware that use C15 power connectors.

Features

Safe, Reliable Power Solution

- . Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- · Recommended for Cisco, HP and other C15-compatible hardware

Color-Coded Cable and Connectors

• Colored orange for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- · Flexible SJT jacket
- 250V/15A rating
- UL-listed

Specifications





INPUT Cable Length (ft.) 3 Cable Length (m) 0.9 Cable Length (in.) 36 PHYSICAL Color Orange ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY Product Warranty Period (Worldwide) Lifetime limited warranty		
Cable Length (in.) Cable Length (in.) PHYSICAL Color Orange ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C15 WARRANTY	INPUT	
Cable Length (in.) 36 PHYSICAL Color Orange ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (ft.)	3
PHYSICAL Color Orange ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (m)	0.9
Color Orange ENVIRONMENTAL Operating Temperature Range -4 F to 221 F (-20 TO 105 C) Storage Temperature Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15	Cable Length (in.)	36
ENVIRONMENTAL Operating Temperature Range	PHYSICAL	
Operating Temperature Range	Color	Orange
Storage Temperature Range -4 F to 221 F (-20 TO 105 C) Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	ENVIRONMENTAL	
Operating Humidity Range 10-85% RH Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Operating Temperature Range	-4 F to 221 F (-20 TO 105 C)
Storage Humidity Range 10-85% RH CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Storage Temperature Range	-4 F to 221 F (-20 TO 105 C)
CONNECTIONS Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Operating Humidity Range	10-85% RH
Side A - Connector 1 IEC-320-C14 Side B - Connector 1 IEC-320-C15 WARRANTY	Storage Humidity Range	10-85% RH
Side B - Connector 1 IEC-320-C15 WARRANTY	CONNECTIONS	
WARRANTY	Side A - Connector 1	IEC-320-C14
	Side B - Connector 1	IEC-320-C15
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY	
	Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies