

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

3.2-3.8kW Single-Phase Metered PDU, 200-240V Outlets (6-C19 & 32-C13) C20/L6-20P Cable 10ft Cord, 0U Vertical

MODEL NUMBER: PDUMV20HV





Description

Tripp Lite single phase Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital display. Enables visual monitoring of PDU load levels to prevent overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- 16/20A single phase 200-240V Metered Power Distribution Unit / PDU (Agency derated to 16A continuous)
- Two-digit lighted meter reports combined total output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 0U 63.75in / 162cm vertical rackmount format installs using no rack spaces
- 38 total outlets (6 C19, 32 C13)
- Installable cord retention brackets keep vital networking equipment plugged in
- Toolless installation supported in button-mount compatible equipment racks
- Bolt-down installation brackets support installation in other racks and additional surfaces

Highlights

- Metered single phase 16/20A 200-240V 0U 63.75in / 162cm vertical rackmount PDU
- Two-digit meter reports output current in amps
- 10ft / 3m detachable input cable with NEMA L6-20P plug
- C20 inlet accepts a variety of 16A international cordsets
- 38 output receptacles (6 C19, 32 C13) with cord retention brackets
- Toolless button mount and bolt-down bracket installation hardware included

Applications

 Ideal means of powering networking equipment in datacenters, computer rooms and network closets

Package Includes

- PDUMV20HV 63.75 inch basic
 PDU with owner's manual
- Set of 2 bolt-on plug retention brackets and installation hardware
- Set of mounting brackets and installation hardware

Specifications

OVERVIEW	
PDU Type	Metered
ОИТРИТ	



	T	
Output Capacity Details	3.3kW (208V input), 3.5kW (220V input), 3.7kW (230V input), 3.8kW (240V input), 3.2kW (200V input); 20A maximum (agency de-rated to 16A continuous)	
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(32) C13; (6) C19	
Output Nominal Voltage	200-240V nominal, single phase	
Overload Protection	Outlets are arranged in a single unbreakered load bank	
Outlet Type	IEC-C13, IEC-C19	
Individual Outlet Switching	No	
INPUT		
PDU Input Voltage	200; 208; 220; 230; 240	
Maximum Input Amps	20	
Maximum Input Amps Details	Agency de-rated to 16A continuous	
Input Connection Type	L6-20P detachable cordset, C20 inlet available	
PDU Plug Type	NEMA L6-20P; IEC-320 C20	
Input Cord Length (ft.)	10	
Input Cord Length (m)	3.05	
Input Phase	Single-Phase	
USER INTERFACE, ALERTS & CO	NTROLS	
Front Panel LEDs	Includes built-in 2-character LED meter to display whole PDU power consumption	
Switches	n/a	
PHYSICAL		
Shipping Dimensions (hwd / in.)	64.5 x 3.5 x 4.75	
Shipping Dimensions (hwd / cm)	163.8 x 8.9 x 12.1	
Shipping Weight (lbs.)	6	
Shipping Weight (kg)	2.8	
Unit Dimensions (hwd / in.)	63.75 x 2.25 x 3.75	
Unit Dimensions (hwd / cm)	162 x 5.7 x 9.5	
Unit Weight (lbs.)	5.2	
Unit Weight (kg)	2.4	
Material of Construction	Aluminum	
Form Factors Supported	Ou vertical installation in equipment racks, plus under-counter and wallmount	
PDU Form Factor	Vertical (0U)	
ENVIRONMENTAL 2/3		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Relative Humidity	0-95% non-condensing	
CERTIFICATIONS		
Certifications	Tested to UL60950-1 (USA, Canada), NOM (Mexico), CE (IEC 60950)	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies