

## For Patient-Care Vicinity – UL 1363A Medical-Grade Power Strip with 4 15A Hospital-Grade Outlets, 15 ft. Cord

MODEL NUMBER: PS-415-HG-OEM



### Description

### Features

- Ideal for use in operating rooms, patient-care vicinities, therapy rooms, imaging environments and administrative areas
- For use on IV poles, mobile carts, crash carts and mobile workstations, when properly mounted
- 120V, 50/60 Hz power strip complies with UL 1363A specifications
- 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power
- 15 ft. power cord provides ample reach to the power source
- Rugged, all-metal housing for long life in demanding environments
- Dual, resettable built-in 15A circuit breakers protect against dangerous overloads
- Switchless design prevents accidental shut-off
- Includes four locking outlet covers that require a tool to remove
- Built-in mounting tabs and flanges make the PS-415-HG-OEM easy to install on a variety of surfaces
- Silver ionic powder coating is 99.9% effective in inhibiting the growth of bacteria like C. diff and MRSA
- Patented coating helps to reduce the risk of healthcare-acquired infections (HAIs) in hospitals and other medical environments

### Highlights

- Approved for use in patient-care vicinities when properly mounted
- Complies with UL 1363A specifications
- Features 4 NEMA 5-15R-HG hospital-grade outlets with optional locking outlet covers
- Includes 15 ft. cord with NEMA 5-15P-HG hospital-grade plug
- Easy to mount on a variety of surfaces
- Exclusive, patented anti-microbial coating - 99.9% effective in inhibiting bacteria and viruses

### Package Includes

- PS-415-HG-OEM UL 1363A Medical-Grade Power Strip with four 15A Hospital-Grade Outlets and 15 ft. Cord
- Kit of four optional, reusable locking outlet covers
- Owner's Manual with maintenance requirements



- Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

## Specifications

| MODEL TEXT                         |  |
|------------------------------------|--|
| What Does This Product Do?         | Supplies power to movable plug-connected components mounted to IV poles, mobile carts, crash carts and mobile medical workstations in operating rooms and patient-care vicinities. |
| OUTPUT                             |  |
| Frequency Compatibility            | 50 / 60 Hz   |
| Output Receptacles                 | (4) 5-15R-HG   |
| Circuit Breaker (amps)             | 15   |
| Overload Protection                | 2 x 15amp breakers (1 line, 1 neutral)   |
| Outlet Orientation                 | Single row of 4  |
| Right-Angle Outlets                | No   |
| INPUT                              |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 15A, 120V  |
| Input Connection Type              | NEMA 5-15P-HG  |
| Input Cord Length (ft.)            | 15   |
| Input Cord Length (m)              | 4.57   |
| Input Cord Gauge Type              | 14 gauge, SJT  |
| Voltage Compatibility (VAC)        | 120  |
| Voltage Compatibility (VDC)        |  |
| USER INTERFACE, ALERTS & CONTROLS  |  |
| Switches                           | No power switch  |
| PHYSICAL                           |  |
| Shipping Dimensions (hwd / in.)    | 2.400 x 9.700 x 6.300  |
| Shipping Dimensions (hwd / cm)     | 6.10 x 24.64 x 16.00   |
| Shipping Weight (lbs.)             | 2.9000   |
| Shipping Weight (kg)               | 1.32   |
| Unit Dimensions (hwd / in.)        | 8.65 x 2.5 x 1.5   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|  |   |
|--|---|
| Unit Dimensions (hwd / cm)                           | 21.97 x 6.35 x 3.81   |
| Unit Weight (lbs.)                                   | 2.25  |
| Unit Weight (kg)                                     | 1.02  |
| Material of Construction                             | Metal   |
| Integrated Keyhole Mounting Tabs                     | Keyhole mounting tabs and flanges enable mounting to a variety of surfaces  |
| Receptacle Color                                     | WHITE   |
| Color (AC Line Cord)                                 | White   |
| Outlets Measurement (Center to Center)               | Inner outlets = 32.5mm  |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm |
| Anti-Microbial Protected                             | Yes   |
| <b>CERTIFICATIONS</b>                                |   |
| Approvals  | TUV tested to UL 1363A  |
| <b>WARRANTY</b>                                      |   |
| Product Warranty Period (Worldwide)                  | Lifetime limited warranty   |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>