

Model #: TLP6B

6 outlet, 6-ft cord, 360 joules Protect It! Surge Suppressor



Highlights

- 6 outlet / 6-ft cord
- 360 joule rating
- \$10,000 Ultimate Lifetime Insurance (US & Canada only)

Description

Tripp Lite's TLP6B offers economical AC surge suppression for protection of workstations, desktop PC's, telecom systems and other sensitive Tripp Lite's TLP6B offers economical AC surge suppression for protection of workstations, desktop PC's, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP6B offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 360 joules shields equipment from surges and line noise. Attractive black suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$10,000 Ultimate Lifetime Insurance (US & Canada only).

PLUG/OUTLETS: Input: NEMA5-15P / Output: 6 NEMA5-15R / 6-ft AC line cord ELECTRICAL: 120V AC, 60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet SUPPRESSION: AC: 150V RMA Clamping / 360 joules/ 500V UL1449 3rd Edition

Applications

• Ideal for any desktop, network or home computing application requiring AC line protection

Package Includes

• TLP6B surge suppressor

Features

- 6 outlets
- 6-ft cord
- Surge suppression rating: 360 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green "Protected" LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- · Lighted power switch
- \$10,000 Ultimate Lifetime Insurance (US & Canada only)
- Lifetime product warranty

Specifications

OVERVIEW

Frequency compatibility Output watts 1875 Circuit Breaker (amps) 15 Overload protection 15A resettable illuminated combo switch / circuit breaker Outlet quantity / type 6 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformer stotal Outlet orientation Single row of 6 outlets INPUT Recommended Electrical Service 120V (110-125V) Service Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response L-N Clamping voltage (RMS) 150 UL1499 let through rating DATALINE SURGE SUPPRESSION DATALINE SURGE SUPPRESSION	Intended Application	Home / Office	
Output watts 1875 Circuit Breaker (amps) 15 Overload protection 15A resettable illuminated combo switch / circuit breaker Outlet quantity / type 6 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total Outlet orientation Single row of 6 outlets INPUT Recommended Electrical 120V (110-125V) Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response 1-1 ns Imput condes 1-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	ОИТРИТ		
Circuit Breaker (amps) Overload protection 15A resettable illuminated combo switch / circuit breaker Outlet quantity / type 6 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total Outlet orientation Single row of 6 outlets INPUT Recommended Electrical Service 120V (110-125V) Service Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating up to 20dB DATALINE SURGE SUPPRESSION	Frequency compatibility	60 Hz	
Overload protection 15A resettable illuminated combo switch / circuit breaker Outlet quantity / type 6 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total Outlet orientation Single row of 6 outlets INPUT Recommended Electrical 120V (110-125V) Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time 150 L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Output watts	1875	
Outlet quantity / type 6 NEMA 5-15R Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total Outlet orientation Single row of 6 outlets INPUT Recommended Electrical \$120V (110-125V)\$ Service NEMA 5-15P Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression response time 4 1 ns time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500V EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Circuit Breaker (amps)	15	
Transformer accommodation Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total Outlet orientation Single row of 6 outlets INPUT Recommended Electrical Service Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Overload protection	15A resettable illuminated combo switch / circuit breaker	
Outlet orientation Single row of 6 outlets INPUT Recommended Electrical Service 120V (110-125V) Recommended Electrical Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time 2-1 ns Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Outlet quantity / type	6 NEMA 5-15R	
Recommended Electrical Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time 150 L-N Clamping voltage (RMS) 150 UL1499 let through rating 500V EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Transformer accommodation	Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total	
Recommended Electrical Service 120V (110-125V) Input connection type NEMA 5-15P Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL 1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Outlet orientation	Single row of 6 outlets	
Input connection type Input cord length (ft.) Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	INPUT		
Input cord length (ft.) 6 Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Recommended Electrical Service	120V (110-125V)	
Input cord gauge, type 14 gauge, SJT Voltage compatibility (VAC) LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Input connection type	NEMA 5-15P	
Voltage compatibility (VAC) 120 LEDS ALARMS & SWITCHES Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time	Input cord length (ft.)	6	
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time	Input cord gauge, type	14 gauge, SJT	
Switches Combination AC circuit breaker and 2 position red illuminated on/off power switch Biagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating AC suppression response time Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Voltage compatibility (VAC)	120	
Diagnostic LEDs Built-in LED confirms suppressor "protection present" (green) status SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time	LEDS ALARMS & SWITCHES		
SURGE / NOISE SUPPRESSION AC suppression joule rating 360 AC suppression response time < 1 ns Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch	
AC suppression joule rating 360 AC suppression response time < 1 ns Protection modes	Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status	
AC suppression response time <1 ns Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	SURGE / NOISE SUPPRESSION		
Protection modes L-N Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	AC suppression joule rating	360	
Clamping voltage (RMS) 150 UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	AC suppression response time	< 1 ns	
UL1499 let through rating 500v EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Protection modes	L-N	
EMI / RFI filtering up to 20dB DATALINE SURGE SUPPRESSION	Clamping voltage (RMS)	150	
DATALINE SURGE SUPPRESSION	UL1499 let through rating	500v	
	EMI / RFI filtering	up to 20dB	
Cable (Coax) Protection No	DATALINE SURGE SUPPRESSION		
	Cable (Coax) Protection	No	
	Network (Ethernet) Protection	No	
PHYSICAL	PHYSICAL		
Shipping weight (lbs) .86	Shipping weight (lbs)	.86	
Unit Dimensions (HWD/in) 11.25 x 3.77 x 1.10	Unit Dimensions (HWD/in)	11.25 x 3.77 x 1.10	
	Shipping Dimensions (HWD/in)	9.21 x 3.77 x 1.10	
Unit weight (lbs) .81	Unit weight (lbs)	.81	

Material of construction	Plastic	
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting	
Receptacle Color	Black	
AC line cord color	Black	
Style	Strip	
CERTIFICATIONS		
Additional International Approvals	RoHS	
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5020.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.