

Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA

Telephone: 773.869.1234 www.tripplite.com

USB 3.0 SuperSpeed Active Extension Repeater Cable (USB-A M/F), 20 m (65 ft.)

MODEL NUMBER: U330-20M











Description

Tripp Lite's U330-20M USB 3.0 SuperSpeed Active Extension Repeater Cable (M/F) increases the length of a device cable up to 65 feet with no worry of signal loss. By daisy-chaining two cables while using external power, you can extend the length between USB devices up to 130 feet.

Connect the male plug to a USB port on your computer or hub and the female end to a USB device cable. A built-in bus-powered signal booster ensures peak performance. Backward compatible with previous USB generations, this cable supports data transfer rates up to 5 Gbps.

Highlights

- Daisy-chain 2 cables for max distance up to 130 ft.
- Supports data transfer rates up to 5 Gbps
- Built-in signal booster for peak performance
- Provides up to 500mA of power to connected device
- Backward compatible with previous USB generations

System Requirements

- USB 3.0 computer port and USB 3.0 device required to meet USB 3.0 speeds
- 5V, 2A power supply with 3.5 x
 1.35 mm DC jack required for power applications above
 500mA. Output plug requires positive tip and negative sleeve.

Package Includes

 U330-20M USB 3.0 SuperSpeed Active Extension Repeater Cable (M/F), 20 m

The U330-20M works with all computers, devices and cables with USB-A connectors. It provides up to 500mA of power to a connected device (a 5V, 2A external power supply is required for power applications stronger than 500mA).

Premium foil and braid shielding delivers top-of-the-line signal quality and protection from EMI/RFI interference. Nickel-plated USB connectors with gold-plated copper contacts ensure excellent conductivity. Integral strain relief ensures the cable and connectors last a long time.

Features

Extends Connections Between 2 USB-A Devices and/or Cables

- Increases length of device cable up to 65 ft.
- Daisy-chain 2 cables for maximum distance up to 130 ft. (while using an external 5V, 2A power supply)
- Supports data transfer rates up to 5 Gbps
- Built-in bus-powered signal booster for peak performance
- Provides up to 500mA of power to connected device
- Backward compatible with previous USB generations

Premium Construction for Superior Signal Transfer

• Premium foil and braid shielding protects against EMI/RFI



- Nickel-plated connectors with gold-plated copper contacts ensure excellent conductivity
- Works with all computers, devices and cables with USB-A connectors
- 5V, 2A external power supply required for power applications stronger than 500mA

Specifications

INDUT	
INPUT	
Cable Length (ft.)	65.6
Cable Length (m)	20
PHYSICAL	
Color	Black
CONNECTIONS	
Side A - Connector 1	USB 3.0 A (MALE)
Side B - Connector 1	USB 3.0 A (FEMALE)
CERTIFICATIONS	
Certifications	RoHS Compliant
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies