Dual 4K Output Module for CORIOmaster®

CM-HDMI-4K-SC-2OUT

OVERVIEW

The Dual HDMI scaled output module allows you to deliver a single 4K60 or dual independent outputs up to 4K30. A new cloning feature allows the second output to be used as a clone of output 1 and can be used up to and including 4K60.



Designed For

C3-540 CORIOmaster, C3-510 CORIOmaster mini, C3-503 CORIOmaster micro	Module installs in to any of the output slots
---	---

Max Installable

CORIO master	C3-540 CORIOmaster 14x C3-510 CORIOmaster mini 5x C3-503 CORIOmaster micro 2x
---------------------	---

Constraints

None	Can be installed with other types of modules in the same system
------	---

SPECIFICATIONS

Output	
Video	2x HDMI 2.0 connectors
Resolution Support	720x480i 59.94 720x480p 59.94 720x576i 50 720x576p 50 1280x720p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 1920x1080i 50, 59.94, 60 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 3840x2160p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
Compatibility	HDMI 2.0 and HDCP 1.4
Color space	BT.601 on standard resolutions BT.709 for HD and UHD
Warranty	Limited warranty: 5 years parts and labor
Regulatory compliance	FCC, CE, RoHS, UL
Mechanical	
Size (H x W x D	21 x 96 x 170 mm (0.9" x 3.9" x 6.8")
Weight (Net)	160 g (5 oz)

Environmental				
Operating temp	0 °C to 40 °C (32 °F to 104 °F)			
Operating humidity	10% to 85% non-condensing			
Storage temp	-10° to +70° C (+14° to 158° F)			
Storage humidity	10% to 85% non-condensing			
Product item number				
CM-HDMI-4K-SC-2OUT	Dual 4K scaled output module for CORIOmaster			
Associated products				
C3-540 CORIOmaster	4RU chassis			
C3-510 CORIOmaster mini	1RU chassis			
C3-503 CORIOmaster micro	1RU ½ width chassis			

Specifications subject to change without notification

