

Specifications

remove

Specifications for RoboSHOT 12E HDBT OneLINK Bridge Express System for Polycom Codecs

Dimensions & Measurements

Depth

6.75 in (17.14 cm)

Distance

328 in (833.12 cm)

Height

6.94 in (17.63 cm)

Operating Temperature

32° to 104°F (0° to 40°C)

Product Weight

4.85 lbs (2.2 kg)

Width

7.05 in (17.91 cm)

Characteristics & Features

3rd Party Control

- RS232
- Telnet

Bridged Signal

Audio and Video

Browser-based User Interface for Remote Control

Built-in

Camera Type

PTZ

Color

Black

Compatible With

- Polycom
- Vaddio

Control Method

- IR Remote
- Joystick
- RS232
- Telnet
- Web UI

Estimated Room Size

- Large Conference Room
- Large Venue
- Small Conference Room

Extension System

with OneLINK Bridge Express for Polycom

Extension Type

- Camera
- Codec

Field of View

70.2° Wide End to 4.1° Tele End

Field of View Wide

Greater than 70

Focus System

- Auto
- Manual

Gain

- Auto
- Manual

Invertible

Yes

Manufacturer

Vaddio

Max Resolution

1080p 60

Minimum Illumination

- 1 Lux (F1.6)
- 100+ Lux Recommended

OneLINK Bridge adds

- 328ft (100M) Power Video Control Extension
- 3G SDI
- Audio Mixer
- HDMI
- USB 3.0

OneLINK Compatibility

Native

Output Ports

- 3G SDI
- Audio
- HDMI
- IP Streaming
- USB 3 Type B

Pan and Tilt Range

- Pan: $\pm 150^\circ$
- Tilt: $+90^\circ$ to -30°

Pan and Tilt Speed

0.35°/sec to 120°/sec

Pixels

8.51 Megapixel (8.57 Total MP)

Power Cord

US Cord

Power Supply

- 1.36A
- 48VDC

Power Type

OneLINK

Preset Positions

16 Custom Home Position

PTZ Motors

Silent BLDC Direct Drive Motors

Quick-Connect Compatibility

No

Signal Type

- 3G SDI
- Audio
- HDMI
- IP Streaming
- RS 232
- USB 3.0

Solution Type

Camera with Extension

Top Resolution

1080p 60

Tri-Sync Motion

Yes

Warranty

3 years

White Balance

- Auto
- Manual
- One Push

Zoom

12x

Zoom Range

10X to 19X

Certifications & Warranties

Certifications

- CE
- FCC
- TAA

