## ViewSonic<sup>®</sup> LDC027-250

## Key Features

- Customizable screen size with Allin-One design for hassle-free installation
- LED cabinets with a native 16:9 aspect ratio for easy configuration of 4K and FHD resolutions
- Anti-collision, dustproof, and moisture-proof through GOB surface treatment
- Centralized and efficient
  management via LAN control
- Detachable system control box for minimalistic aesthetics and easy access



## Product **Description**

The ViewSonic LDC series is an innovative, customizable All-in-One LED display that offers flexible sizing and effortless installation —all in a single solution. Combine the LDC027-250 LED cabinets to create video walls in diverse aspect ratios and sizes, delivering compelling digital signage that brings your concepts to life. Each cabinet features a native 16:9 aspect ratio, enabling easy display configurations in 4K and FHD resolutions for seamless content display. The display's all-in-one design ensures a hassle-free installation process and intuitive operation. Using Glue-on-Board (GOB) surface treatment technology, the IP54-rated LED modules provide enhanced protection against collision, dust, and moisture — making it ideal for public spaces such as lobbies, shopping malls, and transportation hubs. With its slim 31mm thickness and a control box that can be detached to achieve a 99% screen-tobody ratio, this premium display offers an exceptional viewing experience with sleek aesthetics. Complete with centralized management through LAN connectivity to enhance operational efficiency.

> 1. Speakers 2. HDMI Out 3. SPDIF Out 4. HDMI In\*4 5. LAN 6. Audio Out\*2 7. IR Interface

8. Light Senor
 9. IR Receiver
 10. USB-C
 11. USB-A 3.0
 12. USB-A 2.0
 13. Menu Control:Setting
 14. Menu Control:Enter

Menu Control:Brightness Level
 Power Button
 Indicator Light

Visit Us

www.viewsonic.com

ViewSonic LDC027-250 P2.5 Customizable All-in-One LED Display - Datasheet - ViewSonic Global

Serien Size:      27'      Power Supply Voltage:      2025/2007/04 - 508/01/2 or 2007/2 (vary by contra)        Display Area (mm):      600 (H) x 337.5 (V)      Power Supply Voltage:      2025/2007/04 - 508/01/2 or 2007/2 (vary by contra)        Native Resolution:      240515      Power Consumption:      720 per cabinet: 0.507/2 (vary by contra)        Dancing Wire:      0 Direct view LED      Operating Temperature:      0 - 40 vc        Brightness (max.):      600 n115 (100 levels adjustabe)      Operating Temperature:      0 - 40 vc        Contrast Ratio (typ.):      6500:1      Product Dimensions (WMXD):      75/86/87.307.2 (inclusion)        Orientation:      Landscape      Product Dimensions (WMXD):      75/86/87.307.2 (inclusion)        Contrast Ratio (typ.):      H = 170, V = 170      Power Cord:      x1      x1        Local Storage:      Total S2GB      76/04 (400) to 4K(3804)      YAC (2006 availabe storage)        HDTV Compatibility:      1800, 750, 720, 7108, 10800, 21600      YAC (2006 availabe storage)      YAC (2006 availabe storage)      YAC (2006 availabe storage)      YAC (2006 availabe storage)        NPTO <t< th=""><th></th><th></th><th>ic All-III-Offic EED Display - Datasite</th><th></th></t<>			ic All-III-Offic EED Display - Datasite	
Diplay Area (nm):600 (h) × 337.5 (V)Power Supply Voltage:220-240 (Virally to country)Native Resolution:240x135Power Cansumption:7/W per cabinet, 6.05 (Wirally to country)Panel Technology:Direct vew LEDDerating Temperature:0-40°CLED Packago Typo:SMD 3 in 1 (GOB)[Derating Temperature:0-40°CBrightness (max.):600 nits (100 levels adjustabe)Net Weight:110.23 lbsContrast Ratio (typ.):600 nits (100 levels adjustabe)Net Weight:110.23 lbsContrast Ratio (typ.):H = 170, V = 170STANDARD ACCESSORIES100.020 hoursLocal Storage:100.000 hoursPower Corte:x1Local Storage:100.000 hoursPower Corte:x1Emedded OS:Android 9.0Resolution:x1Resolution Support:21606/000.0164 (R300 hoursRemote Controi:x1Vertical Scan Rate:58/C, 720, 1080 PSpare Paris:LED Indute 7%HOT/ Compatibility:21606/000.0164 (R300 hoursSpare Paris:LED Module 7%NPUT'''''''Status''''Spare Paris:LED Module 7%HOM:21606/000.0164 (R300 hours10.04K-004 hours'''LO-MK-004 hours'''USB Type A:'''''''''''Status'''Maintenance Tool:L''''L''''L''''HOM:21606 P''''''''''''USB Type A:''''''''Status'''USB Type A:X''Stared Will USB inputL'''''Spare A: <td>SPECIFICATION</td> <td></td> <td>OTHERS</td> <td></td>	SPECIFICATION		OTHERS	
Native Resolution:240x135Power Consumption:71% Wer (ability,        			Power Supply Voltage:	220-240V/15A ~ 50Hz
Panel Echonology:      Direct view LED        Deckage Type:      SMD 3 in 1 (GOB)      Operating Temperature:      0-40°C        EDD Package Type:      SMD 3 in 1 (GOB)      LED Module Quantity:      2 per cabinet        Brightness (max.):      600 nits (100 levels adjustable)      Net Weight:      11.023 lbs        Orientation:      Landscape      Product Dimensions (WMHzD)      2607 337.8 37.8 m) per cabinet        Viewing Anglies (typ.):      H = 170, V = 170      TANDARD ACCESSORIES      2607 337.8 37.8 m) per cabinet        Usen Storage:      Telal 32GB      Power Cord:      x1      2000 337.8 37.8 m) per cabinet        Usen Storage:      Telal 32GB      Power Cord:      x1      2000 337.8 37.8 m) per cabinet        Usen Storage:      Telal 32GB      Power Cord:      x1      2000 337.8 37.8 m) per cabinet        Embedded OS:      Android 9.0      Remote Control:      x1      2000 300 307.8 7.7 m) per cabinet        HDTV Compatibility:      2800 p.756p. 720p. 1080p.      21000      2000 2000 2000 2000 2000 2000 2000 200	Native Resolution:		Power Consumption:	77W per cabinet,
LED Package Type:      SMO 3 in 1 (GOB)        Bonding Wire:      Copper        Binghtmess (max.):      600 nits (100 levels adjustable)        Brightness (max.):      600 nits (100 levels adjustable)        Orientation:      Landscape        Wawing Angles (typ.):      H = 170, V = 170        Stabulation:      Landscape        Wawing Angles (typ.):      H = 170, V = 170        Stabulation:      Contrast (2000)        Local Storage:      Total 32CB (2006 available storage)        Embedded OS:      Android 9.0        Resolution Support:      2/Sto@deb/Adb va80) to 4K(3840 v 2160g 600 x337.5 x 31mm) per database storage)        HDTV Compatibility:      480p, 578p, 720p, 1080P, 2160g 600 x337.5 x 31mm) 2000        HOTV Compatibility:      480p, 578p, 720p, 1080P, 2160g 600 x337.5 x 31mm) 2000        HDTV Compatibility:      480p, 578p, 720p, 1080P, 2160g 600 x337.5 x 31mm) 2000        Wertial Scan Rate:      56-35Hz        NPUT      LD-MK-004 x1 LD-MK-004	Panel Technology:	Direct view LED	Operating Temperature:	, , , , , , , , , , , , , , , , , , ,
Bonding Wire:      Copper        Pixel Pitch (mm):      2.5        Ingress Protection Rating:      IP54(Front)        Bighines (max):      600 nits (100 levels adjustable)      Net Weight:      (1023 lbs (500) per cabinet)        Contrast Ratio (typ.):      Endscape      Product Dimensions (WxHxL)      26 52x13 29x1 2 inches (500) x337.5 x 3 mm) per cabinet        Viewing Angles (typ.):      H = 170, V = 170 <b>TANDARD ACCESSORIES</b> Impound (000) 337.5 x 3 mm) per cabinet        Local Storage:      Total 326B available storage)      [Alc Cels (Cat 5E):      x1        Local Storage:      Yadio 9.0      LAN Cable (Cat 5E):      x1        Resolution Support:      Yadio 9.0      X1      (Installation guide)        HDTV Compatibility:      2400, 576p, 720p, 1080p, 21000      Yadio 400 (300)      Yadio 400 (300)        NPUT      Yadio 400, 576p, 720p, 1080p, 21000      Yadio 400 (300)      Yadio 400 (300)        NPUT      Yadio 20, 1020 (101)      Yadio 400, 576p, 720p, 1080p, (Internal x3 + external x1)      Yadio 400, 500 (100)        Vertical Scan Rate:      X2      Yadio 400 (101, 400)      Yadio 400, 500 (100)        NUSB Type A:      X2      Xadio aniy)      LD=MIX-0006	LED Package Type:	SMD 3 in 1 (GOB)		
Pikel Piko (mm):      2.5        Brightness (max.):      600 nits (100 levels adjustable)      Net Weight:      11.023 lbs (5kg) per cabinet        Orientation:      Landscape      Product Dimensions (WxHxD):      23.627.13.29.14.8.1        Viewing Angles (typ.):      H = 170, V = 170      STANDARD ACCESSORIES      23.627.13.29.14.8.1        Local Storage:      Total 32G8 (2GGB available storage)      Power Cord:      x1      x1        Embedded OS:      Android 9.0      Resolution Support:      24696, 8769, 7209, 10809, 21600000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 21600000, 216000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 2160000, 216000, 2160000, 216000, 216000, 216000, 216000, 216000, 216000, 216000, 216000, 216000, 2160000, 216000, 216000, 2160000, 2160000, 216	Bonding Wire:	Copper	•	•
Binghness (max.):      000 lits (100 levels adjustable)      Net weight:      (6kg) per cabinet        Contrast Ratio (typ.):      6500:1      Product Dimensions (WXH2):      23.62x13.29x1.2 inches (200 x 377 x 31mm) per cabinet      23.62x13.29x1.2 inches (200 x 377 x 31mm) per cabinet        Viewing Angles (typ.):      H = 170, V = 170      FXNDARD ACCESSORIES      x1        Local Storage:      Toil 32CB (2608 varilable storage)      Power Cord:      x1      x1        Embedded OS:      Android 9.0      Kenote Control:      x1      x1        Resolution Support:      2160@60h2      2160@60h2      QSG:      x1      (Installation guide)        HDTV Compatibility:      2160@60h2      2160@60h2      QSG:      x1      (Installation guide)        Vertical Scan Rate:      56-85fz      Wall Mount:      x1      U.D-MK-006 x1      U.D-MK-006 x1        NPUT      X2      (Instantax 3 + external x1)      Maintenance Tool:      U.D-MK-006      U.D-MK-006        RuS Type A:      x1      (Instantax 2. control x1)      Sinter statistics (Sinter statistics (Sinte	Pixel Pitch (mm):	2.5	ingress i fotostori rtating.	, , , , , , , , , , , , , , , , , , ,
Orientation:      Landscape      Product Dimensions (WXHXD):      (600 x 337.5 x 3 mm) per cabinet        Viewing Angles (typ.):      H = 170, V = 170      STANDARD ACCESSORIES        LED Lifetime (typ.):      100,000 Hours      Power Cord:      x1        Local Storage:      Total 32GB (2608 available storage)      Power Cord:      x1        Embedded OS:      Android 9.0      Resolution Support:      X10xclassoria        VGA(640 x 460) to 4K(3840 x 2160ge0h2)        HOTV Compatibility:      480p. 576p. 720p. 1080p. 2160p      X1 (Installation guide)        Vertical Scan Rate:      056.5H2      VGAIMount:      X1        NPUT      VTOINAL ACCESSORIES      UD-MK-004 x1 (Intermal x3 + external x1)      UD-MK-004 x1 (Intermal x3 + external x1)        USB Type A:      X2 (USB3.0 x1, USB2.0 x1)      Maintenance Tool:      UD-MK-004 (support 4x4/4x/5/xk/d) (support 4x4/4x/5/xk/d) (	Brightness (max.):	600 nits (100 levels adjustable)	Net Weight:	
Orientation:      Landscape      Indicate and the section of the	Contrast Ratio (typ.):	6500:1	Product Dimensions (WxHxD):	(600 x 337.5 x 31mm) per
LED Lifetime (typ.):100.000 HoursPower Cord:x1Local Storage:Total 32GB (28GB available storage)LAN Cable (Cat SE):x1Embedded OS:Android 9.0Resolution Support:VGA(640 x 480) to 4K(3840 x 2160@60hz)Remote Control:x1Resolution Support:VGA(640 x 480) to 4K(3840 x 2160@60hz)Wall Mount:x1HDTV Compatibility:840p. 576p. 720p. 1080p. 2160pWall Mount:x1Horizontal Frequency:31K-94KHzWall Mount:x1Vertical Scan Rate:56-85HzDomdule 7%Domdule 7%NPUT*********************************	Orientation:	Landscape		
Local Storage:Total 32GB (26GB available storage)LAN Cable (Cat 5E):x1Embedded OS:Android 9.0KResolution Support:YGA(640 x 480) to 4K(3840 x 2160@60hz)Remote Control:x1Resolution Support:YGA(640 x 480) to 4K(3840 x 2160@60hz)Wall Mount:x1HDTV Compatibility:480p. 576p. 720p. 1080p. 2160pWall Mount:x1Horizontal Frequency:31K-94KHzWall Mount:x1Vertical Scan Rate:56-85HzMaintenance Tool:LD-MK-004 x1NPUT*********************************	Viewing Angles (typ.):	H = 170, V = 170	STANDARD ACCESSORIES	
Laces Istorage:      (26GB available storage)      III Extender Cable:      X1        Embedded OS:      Android 9.0      IIR Extender Cable:      X1        Resolution Support:      (26GB available storage)      IIR Extender Cable:      X1        Resolution Support:      (26GB available storage)      X1      Remote Control:      X1        Horizontal Frequency:      480p. 576p. 720p. 1080p. 2100p      Wall Mount:      X1      X1        Vortical Scan Rate:      56-85Hz      Wall Mount:      X1      LD-MK-004 x1        Vortical Scan Rate:      56-85Hz      Maintenance Tool:      LD-MK-004 x1        Vortical Scan Rate:      56-85Hz      Maintenance Tool:      LD-MK-004 x1        NPUT      Y2      (VSB3.0 x1, USB2.0 x1)      Maintenance Tool:      LD-MK-006        USB Type A:      X1      (Staran)y      Stard/Star/Star/Star/Star/Star/Star/Star/Star	LED Lifetime (typ.):	100,000 Hours	Power Cord:	x1
Embedded OS:Android 9.0Remote Control:x1Resolution Support:VGA(640 x 480) to 4K(3840 x 2150pGGGx1 (installation guide)HDTV Compatibility:480p, 576p, 720p, 1080p, 2150pWall Mount:x1Horizontal Frequency:31K-94kHzWall Mount:LD-MK-004 x1Vertical Scan Rate:68-68HzMaintenance Tool:LD-MK-004 x1NPUTDYTONAL ACCESSORIESNPUT21(950)Maintenance Tool:LD-MK-004 x1USB Type A:22Maintenance Tool:LD-MK-006 x1Rift:x4(internet 33 + external x1)floor Stand:LD-MK-006Rift:x1D-STND-009 (support 4x/4Ar5/4x6/ 6x4/6x5/6x6)floor Stand:LD-MK-006Rift:x1Cortexfloor Stand:Staffaction floorBMI out:x1X1Staffaction floorfloor Stand:Staffaction floorBMI out:x1X1Staffaction floorStaffaction floorfloor Stand:Speaker:30Wx2X1Staffaction floorStaffaction floorAudio ut (3.5mm):x1Staffaction floor f	Local Storage:			x1
Resolution Support:VGA(640 x 480) to 4K(3840 x 2160@60h2)OSG:x1 (Installation guide)HDTV Compatibility:480p, 576p, 720p, 1080p, 2160pVali Mount:x1Horizontal Frequency:31K-94KH2Vali Mount:LD-MK-004 x1 LD-MK-006 x1Vertical Scan Rate:56-85H2OTIONAL ACCESSORIESNPUTPTIONAL ACCESSORIESNUSB Type A:x1 (UBS3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-004 LD-MK-006Rife:x2 (USB3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-004 LD-MK-006Rife:x1 (Internet x2, control x1)Floor Stand:Stand/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad/Ad	Embedded OS:	Android 9.0	IR Extender Cable:	x1
Resolution Support:      2160@60hz)      OSG:      x1 (installation guide)        HDTV Compatibility:      2160@60hz)      Vall Mount::      x1        Horizontal Frequency:      31K-94KHz      Spare Parts:      LED module 7%        Vertical Scan Rate:      56-65Hz      Maintenance Tool:      LD-MK-006 x1        NPUT      TOTIONAL ACCESSORIES      DMK-006 x1      LD-MK-006        NUBS:      X4      (Internal x3 + external x1)      Maintenance Tool:      LD-MK-006        USB Type A:      X2      (USB3.0 x1, USB2.0 x1)      Maintenance Tool:      LD-MK-006        RI45 Input (Internet):      X1      (internet x2, control x1)      Floor Stand:      LD-MK-006        USB Type A:      X1      X1      LD-MK-006      LD-MK-006        USB Type C:      X1      (internet x2, control x1)      LD-MK-006        USB Type C:      X1      (internet x1)      Control (support 4x4/4x5/4x6/ \$x4/\$x5/\$x5/\$k6)      X4/\$x5/\$x5/\$k6)        USB Type A (Power):      X1      (Internal x1)      X1      X1        USB Type A (Power):      Shared with USB input (SVI.0 \$X x1, USB.2 \$X YI.0 \$X x1, USB.2 \$X YI.0 \$X X1, X1      X1      X1		VGA(640 x 480) to 4K(3840 x	Remote Control:	x1
NDTV Compatibility:2160pNameHorizontal Frequency:31K-94kHzSpare Parts:LED module 7%Wertical Scan Rate:56-85HzMaintenance Tool:LD-MK-006 x1NPUTOPTIONAL ACCESSORIESHDMI:(HDMI 2.0, HDCP 2.2) (Internal x3 + external x1)Maintenance Tool:LD-MK-006USB Type A:(USB3.0 x1, USB2.0 x1)Floor Stand:LD-MK-006RJ45 Input (Internet):x3 (Internet x2, control x1)Floor Stand:LD-STND-009 (support 4x4/4x5/4x6/ 5x4/6x5/5x6/ 6x4/6x5/5x6/USB Type C:x1 (data only)Aldato only)LD-STND-009 (support 4x4/4x5/4x6/ 5x4/6x5/5x6/ 6x4/6x5/6x6)DMI out:x1 (HDMI 1.4, HDCP 1.4) (internal x1)X1 (HDMI 1.4, HDCP 1.4) (internal x1)HDMI out:Spaeker:30Wx2Audio out (3.5mm):x2 (SV/1A x1)Shared with USB input (SV/1A x1), SV/0.5A x1, USB- CSV/1A x1)COTTCOLx1(shared with internet)R345 (LAN control):x1(shared with USB A input) (SB Type A (Services):x1(shared with USB A input) (SB Type A (Services):R345 (LAN control):x1(shared with USB A input) (SB Type A (Services):x1(shared with USB A input) (SB Type A (Services):R345 (LAN control):x1(shared with USB A input) (SB Type A (Services):x1(shared with USB A input) (SB Type A (Services):R3232 (DB 9-pin female):x1	Resolution Support:		QSG:	x1 (Installation guide)
Horizontal Frequency:31K-94kHzSpare Parts:LED module 7%Vertical Scan Rate:56-85HzMaintenance Tool:LD-MK-004 x1 LD-MK-006 x1NPUTX4 (HDMI 2.0, HDCP 2.2) (Internal X3 + external X1)Maintenance Tool:LD-MK-004 (ID-ML-004 x1 LD-MK-006 x1USB Type A:X4 (USB3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-004 (ID-ML-004 x1 LD-MK-006 x1RJ45 Input (Internet):X2 (USB3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-004 (ID-MK-006 x1 LD-MK-006RIn:x1LD-MK-004 (Internet x2, control x1)LD-MK-006 (Internet x2, control x1)IR in:x1WI-Fi Input:2.4G/5G HzUSB Type C:x1 (data only)DUTPUTHDMI out:x1 (Internal x1)Spaker:30Wx2Audio out (3.5mm):x2 (SV/IA x1)USB Type A (Power):Shared with USB input (SV0.9A x1, SV0.5A x1, USB- CSV/IA x1)CNTROLR145 (LAN control):x1 (staned with USB A linput)USB Type A (Services):x1 (staned with USB A linput)R35 (DR 9-pin female):x1 (staned with USB A linput)	HDTV Compatibility:		Wall Mount:	x1
Vertical Scan Rate:56-85HzMaintenance Tool:LD-MK-004 x1 LD-MK-006 x1NPUTOPTIONAL ACCESSORIESHDMI:x4 (HDMI 2.0, HDCP 2.2) (USB3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-006 x1 LD-MK-006 x1USB Type A:x2 (USB3.0 x1, USB2.0 x1)Maintenance Tool:LD-MK-004 x1 LD-MK-006 x1RJ45 Input (Internet):x3 (internet x2, control x1)Maintenance Tool:LD-MK-004 x1 LD-MK-006 x1IR in:x1X1 (internet x2, control x1)IDMintenance Tool:LD-STND-009 (support 4x/4/x5/5x6/ 5x4/5x5/5x6/ 	Horizontal Frequency:	•	Spare Parts:	LED module 7%
NPUTHDMI:x4 (HDMI 2.0, HDCP 2.2) (internal x3 + external x1)Maintenance Tool:LD-MK-004 LD-MK-006USB Type A:x2 			Maintenance Tool:	
HDMI:X4 (HOMI 2.0, HDCP 2.2) (internal x3 + external x1)Maintenance Tool:LD-MK-004 LD-MK-009 (support x4/4x5/4x6/ 5x4/5x5/5x8/ 6x4/6x5/6x8)USB Type A:X2 (USB3.0 x1, USB2.0 x1)Floor Stand:LD-MK-009 (support x4/4x5/4x6/ 5x4/5x5/5x8/ 6x4/6x5/6x8)RJ45 Input (Internet):X1 (internet x2, control x1)Floor Stand:LD-MK-009 (support x4/4x5/4x6/ 5x4/5x5/5x8/ 6x4/6x5/6x8)USB Type C:X1 (data only)(data only)DUTPUTV (internal x1)Multi 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (SV/0.9A x1, SV/0.5A x1, USB- CSV/1A x1)Shared with USB input (SV/0.9A x1, SV/0.5A x1, USB- CSV/1A x1)RJ45 (LAN control):x1 (shared with USB A input) (SV (SU SA x1, SV/0.5A x1, USB- CSV/1A x1)RJ45 (LAN control):x1 (shared with USB A input) (SU SType A (Services):x1 (shared with USB A input) (SS220 (DB 9-pin female):x1 (shared with USB A input)	INPUT		OPTIONAL ACCESSORIES	
Number of the second		(HDMI 2.0, HDCP 2.2)		
RJ45 Input (Internet):x3 (internet x2, control x1)IR in:x1Wi-Fi Input:2.4G/5G HzUSB Type C:x1 (data only)DUTPUTinternal x1)HDMI out:X1 (HDMI 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (SV/0.9A x1, 5V/0.5A x1, USB- C SV/1A x1)CDUTEULRJ45 (LAN control):x1 (shared with USB A input) st (shared with USB A input)RS32 (DB 9-pin female):x1	USB Type A:	x2	Floor Stand:	(support 4x4/4x5/4x6/ 5x4/5x5/5x6/
Wi-Fi Input:2.4G/5G HzUSB Type C:x1 (data only)DUTPUTHDMI out:x1 (HDMI 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input 	RJ45 Input (Internet):			
USB Type C:x1 (data only)DUTPUTHDMI out:x1 (HDM1 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (5V/0.9A x1, SV/0.5A x1, USB- C SV/1A x1)RJ45 (LAN control):x1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	IR in:	x1		
USB Type C:(data only)DUTPUTHDMI out:X1 (HDMI 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (SV/0.9A x1, SV/0.5A x1, USB- C SV/1A x1)CONTROLx1(shared with internet)RJ45 (LAN control):x1(shared with USB A input) x1(shared with USB A input)RS232 (DB 9-pin female):x1	Wi-Fi Input:	2.4G/5G Hz		
HDMI out:x1 (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (5V/0.9A x1, 5V/0.5A x1, USB- C 5V/1A x1)CONTROLx1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	USB Type C:			
HDMI out:(HDMI 1.4, HDCP 1.4) (internal x1)Speaker:30Wx2Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (5V/0.9A x1, 5V/0.5A x1, USB- C 5V/1A x1)CONTROLx1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	OUTPUT			
Audio out (3.5mm):x2USB Type A (Power):Shared with USB input (5V/0.9A x1, 5V/0.5A x1, USB- C 5V/1A x1)CONTROLRJ45 (LAN control):x1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	HDMI out:	(HDMI 1.4, HDCP 1.4)		
USB Type A (Power):Shared with USB input (5V/0.9A x1, 5V/0.5A x1, USB- C 5V/1A x1)CONTROLRJ45 (LAN control):x1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	Speaker:	30Wx2		
USB Type A (Power):(5V/0.9A x1, 5V/0.5A x1, USB- C 5V/1A x1)CONTROLRJ45 (LAN control):x1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	Audio out (3.5mm):	x2		
RJ45 (LAN control):x1(shared with internet)USB Type A (Services):x1(shared with USB A input)RS232 (DB 9-pin female):x1	USB Type A (Power):	(5V/0.9A x1, 5V/0.5A x1, USB-		
USB Type A (Services): x1(shared with USB A input) RS232 (DB 9-pin female): x1	CONTROL			
RS232 (DB 9-pin female): x1	RJ45 (LAN control):	x1(shared with internet)		
	USB Type A (Services):	x1(shared with USB A input)		
IR Receiver: x1	RS232 (DB 9-pin female):	x1		
	IR Receiver:	x1		