

Key Features

- Customizable screen size with Allin-One design for hassle-free installation
- Anti-collision, dustproof, and moisture-proof through GOB surface treatment
- Centralized and efficient management via LAN control
- Detachable system control box for minimalistic aesthetics and easy access
- Ultra-slim design that seamlessly blends into any space



Product **Description**

The ViewSonic LDC series is an innovative, customizable All-in-One LED display that offers flexible sizing and effortless installation—all in a single solution. Combine the LDC031-150 LED cabinet to create video walls in diverse aspect ratios and sizes, delivering compelling digital signage that brings your concepts to life. Its all-in-one design ensures a hassle-free installation process and intuitive operation. Using Glue-on-Board (GOB) surface treatment technology, the IP54-rated LED modules provide enhanced protection against collision, dust, and moisture — making it ideal for public spaces such as lobbies, shopping malls, and transportation hubs. With its slim 31mm thickness and a control box that can be detached to achieve a 99% screen-to-body ratio, this premium display offers an exceptional viewing experience with sleek aesthetics. Complete with centralized management through LAN connectivity to enhance operational efficiency.

1. Speakers 2. HDMI Out 3. SPDIF Out 4. HDMI In*4 5. LAN 6. Audio Out*2 7. IR Interface 8. Light Senor 9. IR Receiver 10. USB-C 11. USB-A 3.0 12. USB-A 2.0 13. Menu Control:Setting 14. Menu Control:Enter Menu Control:Brightness Level
Power Button
Indicator Light

Visit Us

www.viewsonic.com

SPECIFICATION

IR Receiver:

x1

SPECIFICATION		OTHERS	
Screen Size:	31.5"		100-120V/30A ~ 50/60Hz or
Display Area (mm):	640 (H) x 480(V)	Power Supply Voltage:	220-240V/15A ~ 50Hz
Native Resolution:	416x312		(vary by country)
Panel Technology:	Direct view LED	Power Consumption:	105W per cabinet < 0.5W (Hibernate)
LED Package Type:	SMD 3 in 1 (GOB)	Operating Temperature:	0~40°C
Bonding Wire:	Copper	LED Module Quantity:	6 per cabinet
Pixel Pitch (mm):	1.538	Ingress Protection Rating:	IP54(Front)
Brightness (max.):	600 nits (100 levels adjustable)	Net Weight:	13.89 lbs (6.3kg) per cabinet
Contrast Ratio (typ.):	6500:1	Product Dimensions (WxHxD):	25.2x18.9x1.2 inches (640 x 480 x 31mm) per cabinet
Orientation:	Landscape		
Viewing Angles (typ.):	H = 170, V = 170	STANDARD ACCESSORIES	
LED Lifetime (typ.):	100,000 Hours	Power Cord:	x1
Local Storage:	Total 32GB (26GB available storage)	LAN Cable (Cat 5E):	x1
		IR Extender Cable:	x1
Embedded OS:	Android 9.0	Remote Control:	x1
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160@60hz)	QSG:	x1 (Installation guide)
		Wall Mount:	x1
HDTV Compatibility:	480p, 576p, 720p, 1080p, 2160p	Spare Parts:	LED module 7%
Horizontal Frequency:	31K-94kHz	Maintenance Tool:	LD-MK-004 x1
Vertical Scan Rate:	56-85Hz	OPTIONAL ACCESSORIES	
INPUT		Maintenance Tool:	LD-MK-004
HDMI:	x4 (HDMI 2.0, HDCP 2.2) (internal x3 + external x1)	Floor Stand:	LD-STND-009 (support 4x3/4x4/5x3/5x4/6x3/6x4)
USB Type A:	x2 (USB3.0 x1, USB2.0 x1)		
RJ45 Input (Internet):	x3 (internet x2, control x1)		
IR in:	x1		
Wi-Fi Input:	2.4G/5G Hz		
USB Type C:	x1 (data only)		
OUTPUT			
HDMI out:	x1 (HDMI 1.4, HDCP 1.4) (internal x1)		
Speaker:	30Wx2		
Audio out (3.5mm):	x2		
USB Type A (Power):	Shared with USB input (5V/0.9A x1, 5V/0.5A x1, USB-C 5V/1A x1)		
CONTROL			
RJ45 (LAN control):	x1(shared with internet)		
USB Type A (Services):	x1(shared with USB A input)		
RS232 (DB 9-pin female):	x1		
IP Poppivor:	v.1		

Copyright $\ensuremath{\mathbb{C}}$ ViewSonic Corporation 2000-2024. All rights reserved.