





VG2458 - 24" 1080P IPS ERGONOMIC DOCKING MONITOR | 100W USB-C, RJ45, DAISY CHAIN


Key Features



24
DISPLAY



IPS-Type
PANEL



1920 x 1080p
RESOLUTION

Product Description

Elevate your workspace with ViewSonic’s VG2458 docking monitor, designed for seamless connectivity, engineered to streamline your setup with daisy chaining via USB-C. Say goodbye to costly docking stations and cable clutter —our sleek, docking monitor allows you to connect multiple screens with a single cable, delivering stunning visuals while charging your devices simultaneously. Future-ready and versatile, the VG2458 offers a range of connectivity including USB-C with 100W of power delivery, HDMI, DisplayPort, and a 5-port USB hub with a mix of USB-A and USB-C ports to connect peripherals. With full ergonomic adjustability, VG2458 will enhance productivity and comfort, making it the ultimate upgrade for any modern workspace.

Specifications

	More Information
UPC	766907027945
Screen Size	24
Viewable Area (in.)	23.8
Panel Type	IPS-Type
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,500:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit + Hi-FRC)
Aspect Ratio	16:9

Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	1920 x 1080p
Mac® Resolution (max)	1920 x 1080p
USB Type A	3
USB Type C	1x 100W, 2x 15W
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	131
Eco Mode (optimized)	133
Consumption (typical)	138
Consumption (max)	221
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5
Power Supply	Internal
Cable Organization	Yes
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	30 ~ 110 KHz
Frequency Vertical	50 ~ 100 Hz
Height Adjust	150 mm / 5.9 in
Swivel	90º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 30º
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC
Net (lbs)	13.6

Net Without Stand (lbs)	8.6
Gross (lbs)	18
Net (kg)	6.2
Net Without Stand (kg)	3.9
Gross (kg)	8.2
Packaging (in.)	23.6W x 16.1H x 5.6D
Physical (in.)	21.21 W x 15.84 ~ 19.89H x 8.08D
Physical Without Stand (in.)	21.21 W x 12.5H x 1.76D
Packaging (mm)	600W x 410H x 143D
Physical (mm)	538.8W x 402.32~505.22H x 205.27D
Physical Without Stand (mm)	538.8W x 317.51H x 44.75D
Package Contents	LCD Display, Power Cable, DisplayPort Cable, USB Type-C Cable (with USB Type A adaptor), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907027945

Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 ☎

email: salesinfo@viewsonic.com ✉