

Key **Features**

Ultra HD Resolution | Powerful Embedded SOC Platform | All-in-One Solution | RELIABLE 24/7 CONTINUOUS OPERATION | Remote Content Sharing from Anywhere



Product **Description**

The ViewSonic® CDE4320 is a 43" (42.51" viewable) premium 4K large format presentation display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging wherever needed. In addition to HDMI and DVI inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 16GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and its flicker-free and blue light filter technologies help provide a comfortable viewing environment. Bundle includes CDE4320 display, USB Wi-Fi adapter and wall mount.



DISPLAY



RESOLUTION



BRIGHTNESS

m2 24/7

call: 888.881.8781Contact Salesemail: salesinfo@viewsonic.comvisit: viewsonic.com

Display:

Display Type:

LCD

Display Size (in.):

43

Viewable Area (in.):

42.5

Orientation:

Landscape

Colors:

1.078

Color Space Support:

8 bit+FRC

Light Source: DLED

Resolution: 3840 x 2160

Panel Type: IPS-Type

Aspect Ratio: 16:9

Static Contrast Ratio: 1,100:1

Backlight Life (Hours): 40,000

Brightness: 350 cd/m2

Response Time (Typical GTG): 6ms

Bezel Width (in.): 0.51

Bezel Width (mm): 13.0

Viewing Angles: 178° horizontal, 178° vertical

Panel Surface: Hard Coat - Anti-Glare, 3% Haze, 2H with anti-glare treatment

Operation Rating: 24/7

Embedded Player:

OS: Android 8.0

Media Player Type: Media Player

GPU: G51MP2

CPU: Dual CPU - Cortex A73 + A5

CPU Processor Speed: Quad-core, 1.4GHz

Memory: 3GB DDR4
Storage: 16GB

Audio:

Internal Speakers: 10W (x2)

Connector:

HDMI 2.0 (with HDCP 2.2)(2), DVI-D(1), RCA Audio Out(1), 3.5mm Audio In(1), SPDIF Audio Out(1), USB 2.0(2), RS232(1), Ethernet LAN (RJ45)(1), Micro SD Card Slot(1), IR in(1), IR out(1)

100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz

Consumption (max): 85W

Consumption (typical): 70W

Stand-by: <0.5W

Operating Conditions:

Power:

Voltage:

Temperature: 32-104° F (0 - 40° C)

Humidity (non-condensing): 20-80%

Weight (imperial):

Net (lbs): 23.2

Gross (lbs): 29.8

Weight (metric):

Net (kg): 10.5 Gross (kg): 13.5

Dimensions (imperial) (WxHxD):

Packaging (in.): 42.1 x 26.1 x 6.0

Physical (in.): 38.2 x 21.9 x 3.3

Dimensions (metric) (WxHxD):

Packaging (mm): 1070.0 x 663.0 x 153.0

Physical (mm): 969.9 x 558.3 x 84.6

Mount:

VESA Compatible: 400 x 200 mm

Screw Size: M6

General:

AV Control: AMX Certified, Crestron Certified (Version 1.0), Extron Certified

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: CDE4320, Remote control with batteries, Quick Start Guide, Power cable, HDMI

Cable and RS232 cable

Regulations: cULus, FCC, Energy Star, RoHS

Accessories:

NMP309-W, NMP520-W, NMP520-WX, NMP589-W, NMP620-P10, NMP660, STND-056, VB-STND-001, VB-

STND-005, VSB050, WMK-013, WMK-050