

Key Features

Ultra HD Resolution | Embedded SoC Platform | All-in-One Solution | RELIABLE 24/7 CONTINUOUS OPERATION | Remote Content Sharing from Anywhere



Product Description

The ViewSonic® CDE4320 is a 43" (42.51" viewable) premium 4K large format presentation display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging whenever needed. In addition to HDMI and DVI inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 16GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and its flicker-free and blue light filter technologies help provide a comfortable viewing environment. Bundle includes display and USB Wi-Fi adapter.



43"
DISPLAY



3840 x 2160
RESOLUTION



350 cd/m2
BRIGHTNESS

24/7

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Type:	LCD
Display Size (in.):	43
Viewable Area (in.):	42.5
Orientation:	Landscape
Colors:	1.07B
Color Space Support:	8 bit+FRG
Light Source:	DLED
Resolution:	3840 x 2160
Panel Type:	IPS-Type
Aspect Ratio:	16:9
Static Contrast Ratio:	1,100:1
Backlight Life (Hours):	40,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	6ms
Bezel Width (in.):	0.51
Bezel Width (mm):	13.0
Viewing Angles:	178° horizontal, 178° vertical
Panel Surface:	Hard Coat - Anti-Glare, 3% Haze, 2H with anti-glare treatment
Operation Rating:	24/7

Embedded Player:

OS:	Android 8.0
Media Player Type:	Media Player
GPU:	G51MP2
CPU:	Dual CPU - Cortex A73 + A5
CPU Processor Speed:	Quad-core, 1.4GHz
Memory:	3GB DDR4
Storage:	16GB eMMC

Audio:

Internal Speakers:	10W (x2)
--------------------	----------

Connector:

HDMI 2.0 (with HDCP 2.2)(2), DVI-D(1), RCA Audio Out(1), 3.5mm Audio In(1), SPDIF Audio Out(1), USB 2.0(2), RS232(1), Ethernet LAN (RJ45)(1), Micro SD Card Slot(1), IR In(1), IR Out(1)
--

Power:

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption (max):	85W
Consumption (typical):	70W
Stand-by:	<0.5W

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-80%

Weight (Imperial):

Net (lbs):	25.2
Gross (lbs):	29.8

Weight (metric):

Net (kg):	10.5
Gross (kg):	13.5

Dimensions (Imperial) (WxHxD):

Packaging (in.):	42.1 x 26.1 x 6.0
Physical (in.):	38.2 x 21.9 x 3.5

Dimensions (metric) (WxHxD):

Packaging (mm):	1070.0 x 663.0 x 153.0
Physical (mm):	969.9 x 558.3 x 84.6

Mount:

VESA Compatible:	400 x 200 mm
Screw Size:	M6

General:

AV Control:	AMX Certified, Crestron Certified, Extron Certified
Warranty:	Three-year limited warranty on parts, labor and backlight
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
PACKAGE CONTENTS:	CDE4320, Remote control with batteries, Quick Start Guide, Power cable, HDMI Cable and RS232 cable
Regulations:	cULus, FCC, Energy Star, RoHS

Accessories:

NMP309-W, NMP520-W, NMP520-WX, NMP589-W, NMP620-P10, NMP660, STND-036, VS8050, WMK-013, WMK-050
