



IFP6552-2ED - 65" ANDROID EDLA-CERTIFIED VIEWBOARD INTERACTIVE DISPLAY

Key Features


- Android™ EDLA (Enterprise Devices Licensing Agreement) certification
- Advanced Security with Google Workspace
- Full Access to Google Play Store
- · Hassle-free Maintenance and Updates
- Intuitive and Ultra-Responsive Touchscreen







PANEL



RESOLUTION



Product **Description**

The ViewSonic® ViewBoard® IFP6552-2ED is a 65" interactive display with Android™ EDLA (Enterprise Devices Licensing Agreement) certification. With the Android™ EDLA certification, this interactive display delivers optimal performance and seamless integration with the Google ecosystem, including Google Workspace (formerly G Suite for Education) and Google Teams. EDLA also offers access to the full Microsoft 365 suite (including Word, PowerPoint, Teams and more) from the Google Play Store. Teachers can easily access their Google accounts, files, and collaborative tools directly from the ViewBoard display. Plus, with a high-accuracy touchscreen and intelligent IR recognition technology, the IFP6552-2ED delivers an intuitive digital whiteboard experience. 4K Ultra HD resolution delivers optimal images for everyone in the room as well as those learning remotely. In addition, the integrated ViewSonic software suite enables easy content sharing and interactive presentations.

Specifications

UPC	766907025071
os	Android 13 (EDLA)
CPU	Octa-Core CPU (A73*4 + A53*4)
Memory	8GB LPDDR
Storage	64GB eMMC5.0
Microphone	8 array mic (distance: 5M typ., 8M max.)
Internal Speakers	15W (x2)
Subwoofer	15W (x1)
HDMI 2.0 In	3
HDMI Out	1
VGA	1
DisplayPort	1
3.5mm Audio In	1
3.5mm Audio Out	1
SPDIF	1
USB 3.0	3
USB 2.0	5
USB Type C	65W x 1 (front), 100W x 1 (back)
RS232	1
Ethernet LAN (RJ45)	1
Intel® OPS Slot In (80-pin)	1
Voltage	100-240 VAC
Consumption (typical)	91.41
Stand-by	<0.5W
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-80%
Touch Technology	Infrared
Touch Points	Windows: 40, Android: 20
Tip Detection	Dual tips, 2.5mm and 8mm
Other	Object Recognition
Latency	5ms
Net (lbs)	94.8
Gross (lbs)	114.6
Net (kg)	43.0
Gross (kg)	52.0
Packaging (in.)	63.70 x 41.70 x 8.90

59.16 x 37.35 x 4.80 Physical (in.) Packaging (mm) 1618.0 x 1060.0 x 225.0 Physical (mm) 1502.7 x 948.66 x 122.18 **VESA Compatible** 500x400mm M8 **Screw Size** 3-year limited warranty on parts, labor and backlight, onsite warranty Warrantv Recycle/Disposal Please dispose of in accordance with local, state or federal laws. 3m power cord by ship area, Remote control (new VS remote control), 3m touch USB cable, Touch pen x 2, **Package Contents** Quick Start Guide + Compliance statement, RS232 adapter, Clamp x 5, Camera Plate, Screw x 8, HDMI cable 3m, AAA Battery x 2, VB-WIFI-005 adapter Regulations BIS, cTUVus, COC, EPET, ES8 **Ethernet LAN** (10/100/1000M) (USB Type-C 10/100, 1 LAN in and 1 LAN out Android & PC 10/100/1000) Wifi VB-WIFI-005 WiFi Adapter **Display Type** LCD **Screen Size** 65 Viewable Area (in.) 64.5 **Light Source** DLED **Display Resolution** 3840 x 2160 **Refresh Rate** 60Hz **Aspect Ratio** 16:9 **Static Contrast Ratio** 4,000:1 **Dynamic Contrast Ratio** 5,000:1 **Backlight Life (Hours)** 50,000 **Brightness** 350 cd/m2 Response Time (Typical GTG) 6.5ms **Viewing Angles** 178º horizontal, 178º vertical **Panel Surface** Anti-Glare 3H + Anti-Fingerprint 7H

UPC: 766907025071







Contact Sales
ViewSonic.com

888.881.8781 email:
salesinfo@viewsonic.com