


## Key Features

Intuitive and Ultra-Responsive Touchsceen | Front-Facing Soundbar | Built-in Beamforming Microphone | USB-C with Power Delivery | myViewBoard Manager



## Product **Description**

The ViewSonic<sup>®</sup> ViewBoard<sup>®</sup> IFP7552-1C is a 75<sup>"</sup> interactive flat panel display with next-generation whiteboard technologies for immersive learning in any classroom environment. With a high-accuracy touchscreen and intelligent palm recognition technology, the IFP7552-1C delivers an intuitive digital whiteboard experience for everyone from the youngest of students to the most experienced teachers. Featuring 4K Ultra HD resolution, a powerful 45W stereo soundbar with a built-in subwoofer, and microphone array, this ViewBoard display delivers optimal images and sound for everyone in the classroom as well those learning remotely. With the integrated myViewBoard<sup>™</sup> software ecosystem, this ViewBoard display enables teachers to access legacy files from the cloud, as well as build new interactive lessons. IT directors will be confident managing files from a secure cloud network, while curriculum directors will be pleased knowing that this software easily integrates with online resources.





Display:		Operating Conditions:	
Display Type:	LCD	Temperature:	32-104° F (0 - 40° C)
Display Size (in.):	75	Humidity (non-condensing):	10-90%
Viewable Area (in.):	74.5	Touch:	
Light Source:	LED	Touch Technology:	Infrared
Resolution:	3840 x 2160	Touch Points:	Windows: 33-Point Touch, Android: 20-Point Touch
Refresh Rate (Hz):	60	Tip Detection:	Dual tips, 2mm and 9mm
Aspect Ratio:	16:9	Other:	Palm recognition, object awareness
Static Contrast Ratio:	1,200:1	Weight (imperial):	
Dynamic Contrast Ratio:	4,000:1	Net (lbs):	121.8
Backlight Life (Hours):	50,000	Gross (Ibs):	170.8
Brightness:	350 cd/m2	Weight (metric):	
Response Time (Typical GTG):	8ms	Net (kg):	55.3
Viewing Angles:	178º horizontal, 178º vertical	Gross (kg):	77.5
Panel Surface:	G1S, AG glass, 9H pencil hardness, 4mm	Dimensions (imperial) (WxHxD):	
Networking:		Packaging (in.):	72.75 x 46.8 x 10.6
Ethernet LAN:	10/100/1000MB GigaLAN	Physical (in.):	67.3 x 42.2 x 4.7
Wifi:	Optional VB-WIFI-001 adapter, 802.11AX + Bluetooth 5.2	Dimensions (metric) (WxHxD):	
Embedded Player:		Packaging (mm):	1848.0 x 1190.0 x 270.0
OS:	ViewBoard OS based on Android 9.0	Physical (mm):	1709.0 x 1071.0 x 120.0
GPU:	ARM Mali-G52	Mount: VESA Compatible:	800 x 400 mm
CPU:	ARM Quad Core A73	Screw Size:	
CPU Processor Speed:	1.8GHz	General:	M8
Memory:	4GB LPDDR4	Warranty: 3-year limited warranty on parts, labor and backlight, onsite warranty	
Storage:	32GB eMMC	Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.	
Audio:		PACKAGE CONTENTS: IFP7552-1C, Remote control with AAA battery, 3m touch USB cable, Touch pen x	
Microphone:	Beamforming array x 8, noise cancelation	2 (a set), Quick Start Guide + Compliance statement, RS232 adapter, Clamp x 5, Camera Plate, Screw x 8 (camera 2+2, wall mount 4), HDMI cable 3m, Typc-C cable 1.8 (Data & power charged), 3m power cord	
Internal Speakers:	15W (x2)		
Subwoofer:	15W (x1)	Regulations: cTUVus, FCC, ENERGY STAR, EPEAT Silver, Mexico Energy, CE, CB, RoHS, ErP, WEEE	
Connector:		UPC: 766907013924	
HDMI 2.0 In(4), HDMI Out(1), VGA(1), SPDIF(1), USB 2.0(5), USB 2.0 Type B(2), USB 3.1 Type C(1), OPS PC		Accessories:	
Slot(1), RS232(1), Ethernet LAN (RJ45)(2)		NMP760, VB-BLF-003, VB-BLM-003, VB-BLW-003, VB-BOW-001, VB-CAM-001, VB-CAM-002, VB-EBM-001,	
<b>Power:</b> Voltage:	100-240 VAC	VB-EBT-001, VB-EBW-001, VB-STND-001, VB-STND-002, VB-STND-003, VB-STND-004, VB-WIFI-001, VB- WKB-001, VPC12-WPO-6, VPC25-W53-O1-1B, VPC25-W53-O2-1B, VPC27-W55-O2-1B, VPC2C-W33-O1-1B, WMK-047-2	
-			
Consumption (typical):	170W		

Stand-by: <0.5W

Copyright © ViewSonic Corporation 2000-2022. All rights reserved. (06/23/2022 02:27 PM PST)