

Key Features

SuperColor: Amazing Color Accuracy | 3,600 Lumen Brightness

| Energy Efficient SuperEco | Reduced Input Latency



Product Description

The ViewSonic® PA503W price-performance projector features 3,600 lumens, native WXGA 1280x800 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wider color range for lifelike image projection. The PA503W also features extensive connectivity including HDMI, 2 x VGA in, Composite Video, 1 x VGA output, and Audio in/out. An energy-saving SuperEco™ feature reduces power consumption by up to 70%, and extends the lamp life by up to 10,000 hours*. With advanced audiovisual features, flexible connectivity options, and an affordable price, the PA503W is ideal for use in education and small business environments.

*Energy consumption and lamp life may vary based on actual usage and other factors.



- 01. Projection lens
- 02. IR remote sensor
- 03. Elevation foot
- 04. Focus / zoom rings

- 05. VGA x2
- 06. HDMI
- 07. Audio In/Out
- 08. AC In

- 09. Control Panel
- 10. Monitor Out
- 11. Kensington*
- 12. Lock Slot


- 13. Video In
- 14. USB type Mini B
- 15. RS232



**1280 x 800
RESOLUTION**



**3,600
LUMENS**



**1.55~1.70
THROW RATIO**

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:	
Type:	DLP
Resolution Type:	WXGA
Resolution:	1280 x 800
Brightness (ANSI Lumens):	3,600
Throw Distance:	1m-10.98m(100" @3.34m)
Throw Ratio:	1.55~1.70
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Keystone:	Vertical (± 40°)
Lens:	1.1x optical zoom
Light Source (watt):	200
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	10000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22000:1
Aspect Ratio:	16:9

Video Signal:	
Frequency Horizontal:	15K~102KHz

Compatibility:	
PC Resolution (max):	VGA(640 x 480) to FullHD(1920 x 1080)
Mac® Resolution (max):	VGA(640 x 480) to FullHD(1920 x 1080)

Connector:	
3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)	

Audio:	
Internal Speakers:	2W

Power:	
Voltage:	100-240V +/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Operating Conditions:	
Temperature:	32-104° F (0-40° C)

Weight (imperial):	
Net (lbs):	4.89
Gross (lbs):	7.14

Weight (metric):	
Net (kg):	2.2
Gross (kg):	3.24

Dimensions (imperial) (WxHxD):	
Packaging (in.):	14.37 x 11.81 x 7.4
Physical (in.):	11.57x 8.58 x 4.33

Dimensions (metric) (WxHxD):	
Packaging (mm):	365 x 300 x 188mm
Physical (mm):	294 x 218 x 110mm

General:	
Regulations: FCC (including ICES003), cTUVus, NOM, TUV-Rheinland S Mark	

PACKAGE CONTENTS: PA503W projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907904918

Accessories:	