

## Key Features

SuperColor: Amazing Color Accuracy | 3,600 Lumen

Brightness | Energy Efficient SuperEco | Reduced Input

Latency



## Product Description

The ViewSonic® PA503X price-performance projector features 3,600 lumens, native XGA 1024 x 768 resolution, and intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. The PA503X also features extensive connectivity including HDMI, 2 x VGA, VGA out, Composite Video and audio in/out. An energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 15,000 hours\*. With advanced audio-visual features, flexible connectivity options, and an affordable price, the PA503X is ideal for use in education and small business environments.


\*Energy consumption and lamp life may vary based on actual usage and other factors.



1024 x 768  
**RESOLUTION**



3,600  
**LUMENS**



1.96 ~ 2.15  
**THROW RATIO**

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

Type:	DLP
Resolution Type:	XGA
Resolution:	1024 x 768
Brightness (ANSI Lumens):	3,600
Throw Distance:	3.9 ft - 43 ft (100" @13 ft)
Throw Ratio:	1.96 ~ 2.15
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Keystone:	Vertical (± 40°)
Lens:	1.1x optical zoom
Light Source (watt):	190
Light Source Life, Normal (hours):	4500
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22000:1
Aspect Ratio:	4:3

**Video Signal:**

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

**Compatibility:**

PC Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)
Mac® Resolution (max):	VGA (640 x 480) to WUXGA_RB (1920 x 1200)

**Connector:**

Mini USB Type B(1), Audio Output (Mini Jack)(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(1), VGA In(2), VGA Out(1), Composite RCA Video In(1)

**Audio:**

Internal Speakers:	2W
--------------------	----

**Power:**

Voltage:	AC 100-240V (universal), 50-60Hz
Consumption (typical):	260W
Stand-by:	<0.5W

**Operating Conditions:**

Temperature:	32-104° F (0-40° C)
--------------	---------------------

**Weight (imperial):**

Net (lbs):	4.89
Gross (lbs):	7.14

**Weight (metric):**

Net (kg):	2.22
Gross (kg):	6.24

**Dimensions (imperial) (WxHxD):**

Packaging (in.):	14.37 x 11.81 x 7.4
Physical (in.):	11.57 x 8.58 x 4.33

**Dimensions (metric) (WxHxD):**

Packaging (mm):	365 x 300 x 188
Physical (mm):	294 x 218 x 110

**General:**

Regulations:	FCC (including ICES-003), cTUVus
PACKAGE CONTENTS:	PA503X projector, power cable, VGA cable, remote control, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
Warranty:	3-year limited warranty on parts and labor, 1st year free Express Exchange* service**
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
UPC:	766907905113
<b>Accessories:</b>	