Key **Features**

- QHD 2560 X 1440 resolution
- 75Hz FreeSync sync to eliminate screen tearing and reduce stuttering
- Dual 2 watts speakers
- 3-side borderless bezel
- HDMI and DisplayPort inputs for connectivity



Product **Description**

The ViewSonic VA2715-2K-MHD is a 27" 2K monitor with HDMI and DisplayPort input for business or home usage. With a 27" display and 2560 X 1440 resolution that delivers larger and clearer images, the QHD monitor expands your productivity. Delivering a stunning image quality with low power consumption, this monitor provides six ViewMode presets that deliver optimized screen performance based on your needs. FreeSync means no tearing or stuttering even when gaming. The eye care technology that comes standard with all VA monitors helps to eliminate eyestrain from extended viewing periods. A VESA-compatible mount makes this monitor is easy to setup on the wall or with a wide range of industry-standard mounts.

Visit Us www.viewsonic.com

DISPLAY		VIDEO INPUT		
Display Size (in.):	27	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -	
Viewable Area (in.):	27		DisplayPort (v1.2)	
Panel Type:	VA Technology	ERGONOMICS	50 / 200	
Resolution:	2560 x 1440	Tilt (Forward/Back):	-5° / 20°	
Resolution Type:	QHD (Quarter HD)	WEIGHT (IMPERIAL)	7.9	
Static Contrast Ratio:	4,000:1 (typ)	Net (lbs): Net Without Stand (lbs):	6.8	
Dynamic Contrast Ratio:	50M:1	, ,	11	
Light Source:	LED	Gross (lbs):	II	
Brightness:	250 cd/m² (typ)	WEIGHT (METRIC) Net (kg):	3.6	
Colors:	16.7M	Net Without Stand (kg):	3.1	
Color Space Support:	8 bit true	Gross (kg):	5	
Aspect Ratio:	16:9	DIMENSIONS (IMPERIAL) (WXHXD)		
Response Time (Typical GTG):	4ms	Packaging (in.):	27.1 x 17.6 x 5	
Viewing Angles:	178º horizontal, 178º vertical	Physical (in.):	24.1 x 18 x 8.1	
Backlight Life (Hours):	30000 Hrs (Min)	Physical Without Stand (in.):	24.1 x 14.2 x 1.6	
Curvature:	Flat	DIMENSIONS (METRIC) (WXF		
Refresh Rate (Hz):	75	Packaging (mm):	688 x 448 x 128	
Adaptive Sync:	FreeSync	Physical (mm):	613 x 456 x 205	
Blue Light Filter:	Yes	Physical Without Stand (mm):	613 x 361 x 40	
Flicker-Free:	Yes	GENERAL	013 x 301 x 40	
	NTSC: 72% size (Typ) sRGB: 104%	GENERAL	cTUVus, FCC-B, ICES003, Energy	
Color Gamut:	size (Typ)		Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS,	
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	ErP, REACI	ErP, REACH, WEEE, EAC,	
Surface Treatment:	Anti-Glare, Hard Coating (3H)		UkrSEPRO, UKCA, BSMI, RCM, VCCI, PSE	
COMPATIBILITY			VA2715-2K-MHD x1, HDMI Cable	
PC Resolution (max):	2560x1440	PACKAGE CONTENTS:	(v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1	
Mac® Resolution (max):	2560x1440	Recycle/Disposal:	Please dispose of in accordance with	
PC Operating System:	Windows 10/11 certified; macOS tested	Warranty:	local, state or federal laws. *Warranty offered may differ from	
Mac® Resolution (min):	2560x1440	warranty.	market to market	
CONNECTOR		Country Of Origin:	54	
3.5mm Audio Out:	1	Power Management:	Energy Star standards, EPEAT	
HDMI 1.4:	2			
DisplayPort:	1			
Power in:	DC Socket (Center Positive)			
AUDIO				
Internal Speakers:	2Watts x2			
POWER				
Eco Mode (Conserve):	16W			
Eco Mode (optimized):	19W			
Consumption (typical):	22W			
Consumption (max):	31W			
Voltage:	AC 100-240V			
Stand-by:	0.5W			
Power Supply:	External Power Adaptor			
ADDITIONAL HARDWARE				
Kensington Lock Slot:	1			
CONTROLS				
Physical Controls:	U, R, D, L, EN (power)			
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu			
OPERATING CONDITIONS				
Temperature:	32°F to 104°F (0°C to 40°C)			
Humidity (non-condensing):	20% to 90%			
WALL MOUNT				
VESA Compatible:	100 x 100 mm			
INPUT SIGNAL				
Frequency Horizontal:	15 ~ 120KHz			

24 ~ 75Hz

Frequency Vertical: