

## VA2756-4K-MHD - 27" 4K IPS MONITOR WITH HDMI, DISPLAYPORT

## **Key Features**

- 4K Ultra HD Resolution
- SuperClear IPS Panel
- Frameless Edge-to-Edge Screen
- Versatile Connectivity
- Optimized View Settings



**DISPLAY** 





RESOLUTION



Product **Description** 

Featuring enhanced wide-angle viewing, stunning resolution and flexible connectivity options, the ViewSonic® VA2756-4k-MHD monitor is a great addition to any workspace. This 27" VA2756-4k-MHD monitor comes with SuperClear® IPS panel technology so you can experience stunning brightness and contrast at nearly any viewing angle. Featuring 3840 x 2160 resolution and a frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Connect laptops, PCs, gaming consoles and other multimedia devices with HDMI or DisplayPort connectivity. And with powerful features like flicker-free technology and a blue light filter, you can work for longer with less strain. Enjoy a 3 year limited warranty, industry-leading pixel performance policy and so much more with the ViewSonic® VA2756-4k-MHD monitor.

## Specifications

More Information		
UPC	766907005134	
Screen Size	27	
Viewable Area (in.)	27	
Panel Type	IPS	
Display Resolution	3840 x 2160	
Display Resolution	4K (3840×2160)	

Static Contrast Ratio	1,200:1
Light Source	LED
Brightness	400 cd/m2
Colors	1.07B
Color Space Support	8 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	28w
Eco Mode (optimized)	34w
Consumption (typical)	40w
Consumption (max)	54w
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.3w
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 140 KHz
Frequency Vertical	24 ~ 75 Hz
Tilt (Forward/Back)	3° / 20°
Net (lbs)	12.1
Net Without Stand (lbs)	10.4
Gross (lbs)	16.1

Net (kg)	5.5
Net Without Stand (kg)	4.7
Gross (kg)	7.3
Packaging (in.)	24.2 " (W) x 16.9 " (H) x 9.2 " (D)
Physical (in.)	24.2 " (W) x 14.5 " (H) x 2.1 " (D)
Physical Without Stand (in.)	26.7 " (W) x 19.3 " (H) x 6.5 " (D)
Packaging (mm)	614 mm (W) x 430 mm (H) x 233 mm (D)
Physical (mm)	614 mm (W) x 369 mm (H) x 53 mm (D)
Physical Without Stand (mm)	677 mm (W) x 497 mm (H) x 164 mm (D)
Regulations	cTUVus, FCC-B, ICES003, CEC, Energy Star 8.0, EPEAT Silver, NOM, Mexico Energy
Package Contents	LCD Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907005134







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com