

All-in-one conference camera

Key Features

- Automatically focus framing on narrator during the conference through voice tracking.
- Automatically adjust the frame based on attendees' seating with up to 121° wide-angle FOV.
- 4K UHD resolution and 5x digital zooming.
- Multiple mounting options to fit in all meeting room setups.
- Stereo speaker and 4 array microphone with 3A audio (AEC/ANS/AGC) processing technology*



*Remarks:

AEC: Acoustic Echo Cancellation

ANS: Automatic Noise Suppression

AGC: Automatic Gain Control

Product Description

The ViewSonic All-in-one conference camera is designed to enhance the video meeting experience for all the participants. Its 4K UHD resolution and 121° super wide-angle lens efficiently capture the whole room regardless of seating arrangements. The voice tracking feature of its built-in microphone paired with a 5x digital zoom ensures that the speaker will always be inframe. It comes complete with an stereo speaker and a 4 array microphone with noise and echo cancellation technologies to ensure participants can hear and be heard loud and clear.



1. DC in
2. USB-C 3.0
3. HDMI
4. USB-A 2.0
5. LAN

Visit Us  www.viewsonic.com

OPERATING SYSTEM

Windows 7 (only 1080p and below), Windows 8.1, Windows 10 or higher
macOS® 10.10 or higher
Google Chromebook™ Version 29.0.1547.70 or higher
Linux (requires support for UVC)

SYSTEM REQUIREMENT

CPU Recommended: 2.4 GHz Intel® Core 2™ Duo processor or above

RAM Recommended: 2 GB of memory or above

CAMERA

Sensor: 1/2.5 inch, CMOS, 8.51M pixel

Field of View (FOV): 121°(DFOV), 110°(HFOV), 5x Digital Zoom, Pan/Tilt ±15°

White Balance: Automatic, Indoor, Outdoor, One Push, Manual

Digital Noise Reduction: 2D, 3D digital noise reduction

Backlight Compensation: Support

AUDIO

Microphone: Beamforming microphone, pick up distance up to 6 meters

SUPPORTED VIDEO FORMAT

Color System Compression: H.264 / MJPEG / YUY2

Max. Resolution Video: 4K@30fps,
1080P@30fps,
720P@30fps, etc

CONNECTIVITY

USB: 3.0(Type C x1),
2.0(Type A x1)

HDMI output: x1

DIMENSIONS

Physical (W xH xD): 600 x 115 x 135 mm
(bracket included)

WEIGHT

Physical (Net): 2.2 kg (4.86 lbs)

REGULATIONS

Compliance Certification: CE, FCC, IC ID, FCC ID,
LVD

PACKAGE CONTENTS

1. VB-CAM-201
2. Documentation
3. Remote Control
4. Power Adapter
5. Bracket
6. USB Type-C Cable
7. Bracket Screw x 6
8. Wall Anchor x 6