

Key Features

- Instant, secure access to your digital workspace using Windows Hello
- Crystal-clear video with 5MP webcam, privacy cover, dual microphones, and stereo speakers
- 120Hz refresh rate ensures ultra-smooth visuals during meetings and multitasking
- USB-C port simplifies connections for audio, video, and data transfer
- USB 3.2 hub with 1 USB-C upstream, 3 USB downstream ports, HDMI, and DisplayPort inputs for seamless multi-device connectivity



Product **Description**

The VG2741V is a 27" Full HD (1920 x 1080) **USB-C video conferencing monitor with Windows Hello**, designed to deliver secure, high-quality virtual meetings straight out of the box. With **facial recognition login via Windows Hello**, users can sign in quickly and securely—reducing password fatigue and minimizing the risk of visual hacking. A built-in **5MP adjustable webcam**, **dual microphones**, **and dual 2W speakers** provide sharp video and clear audio for professional-grade conferencing. The webcam's **±5° vertical tilt** ensures perfect framing, while the **built-in privacy cover** safeguards user privacy when the camera is not in use. The monitor supports streamlined connectivity with a **USB-C upstream port** for video, audio, and data, plus **HDMI**, **DisplayPort**, **and three USB 3.2 downstream ports**—making it ideal for both home and office environments. With a **120Hz refresh rate** and integrated **Eye ProTech+** technology (low blue light and flicker-free viewing), the VG2741V ensures smooth visuals and greater eye comfort throughout the workday. For additional productivity, it supports **vDisplay Manager** for on-screen control and **vSplit** for efficient window layout management—both available via the **ViewSonic Display Portal**. With **full ergonomic adjustability** including height, tilt, swivel, and pivot, the VG2741V adapts to your setup for long-lasting comfort and flexible workflows.



Visit Us

6 DisplayPort

www.viewsonic.com

13 SMP Camera



Display Size (in.): 27 Vinewable Area (in.): 27 Vinewable Area (in.): 27 Vinewable Area (in.): 27 Vinewable Area (in.): 1920 x 1080 Resolution: 1920 x 1080 Resolution Type: FHD (Full HD) Static Contrast Ratio: 500.11 (typ) Dynamic Contrast 500.11 (typ)	2:16 PM ViewSo	onic VG2741V 27" FHD USB-C Video Confe
Visuable Area (in.): 27 Panel Type: IPS Technology Resolution Type: FHD (Full HD) Static Contract Ratio: 1,500-1 (typ) Dynamic Contract Ratio: 1,500-1 (typ) Upth Source: LED Brightness: 250 cd/m² (typ) Colors: 16-7M Colores: 16-9 Aspect Ratio: 16-9 Response Time (Typeal GTQ): 4.19ma Response Time (GTG wOD): 4.19ma Visiable Refresh Rate Total: 120 Variable Refresh Rate Total: 120 Low Blue Light: Hardware solution Filcker-Free: Yes Color Gamut: MTSC: 278's size (Typ) Filcker-Free: Yes Color Gamut: Arti-Glare, Hard Coating (3H) COMPATIBLITY 1920x1080 COMPATIBLITY 1920x1080 PC Operating System: Windows 10/11 certified; macOS	DISPLAY	
Panel Type: IPS Technology Resolution: 1920 x 1080 Resolution: 1920 x 1080 Resolution: 1920 x 1080 Resolution: 1,500-1 (typ) Pynamic Contrast Ratio: 50M.1 Light Source: LED Brightness: 250 odm* (typ) Colors: 16,7M Color Space Support: 8 bit (6 bit + FRC) Asapec Ratio: 19.9 Response Time (GTG w/OD): 4 ms Asapec Ratio: 19.9 Response Time (GTG w/OD): 4 ms Asapec Ratio: 19.9 Response Time (GTG w/OD): 4 ms Asapec Ratio: 19.9 Response Time (GTG w/OD): 4 ms Asapec Ratio: 178* horizontal, 178* vertical Backlight Life (Hours): 30000 Hrs (Min) Curvature: Flat		
Resolution: 1920 x 1080 Resolution Type: FHD [Fail HD] Static Contrast Ratio: 1,500-1 (typ) Dynamic Contrast Ratio: 50M-1 Light Source: LED Brightness: 250 cd/m² (typ) Colors: 16-7M Colors Space Support: 8 bit (6 bit + FRC) Aspect Ratio: 16-9 Response Time (Typical GTG): 4ms Response Time (GTG W/OD): 4.19ms Viewing Angles: 178* horizontal, 178* vertical Backlight Life (Hours): 30000 Hrs (Min) Curvature: Flat Refresh Rate (Rtc): 120 Variable Refresh Rate Technology: Yes Color Gamut: NTSC: 72% size (Typ) SKGB: 104% size (Typ) SKGB: 104% size (Typ) Pickel Size: 0.311 mm (H) x 3.31 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) COMPATIBILITY 1920x1080 PC Operating System: Windows 10/11 certified; macOS tested MacS Resolution (max): 1920x1080 PC Operating System: 1 (15W po		
Resolution Type: FHD (Full HD) Static Contrast Ratio: 1,500:1 (typ) Dynamic Contrast Ratio: 1,500:1 (typ) Dynamic Contrast Ratio: LED Brightness: 250 cdrim* (typ) Colors: 16.7M Colors: 16.7M Colors: 16.7M Response Time (Typical CTO): 4ms Response Time (GTG w/OD): 4.19ms Viewing Angles: 178* horizontal, 178* vertical Backlight Life (Hours): 30000 Hrs (Min) Curvature: Flat Refresh Rate (Hz): 120 Variable Refresh Rate Technology: Ves Technology: Ves Color Gamut: Rick (File Color File Colo		
Static Contrast Ratio: 1,500.1 (typ)		
Dynamic Contrast Ratio: S0M:1 Light Source: LED		
Light Source: LED		
Brightness	•	
Colors Space Support:		
Color Space Support: 8 bit (6 bit + FRC)		
Aspect Ratio: 16.9 Response Time (Typical GTG): 4ms Response Time (GTG w/OD): 4.19ms Vewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 30000 Hrs (Min) Curvature: Flat Refresh Rate (H2): 120 Variable Refresh Rate Technology: Ves Low Blue Light: Hardware solution Flicker-Free: Ves Color Gamut: NTSC: 72% size (Typ) Pixel Size: 0.311 mm (H) x 0.311 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) COMPATIBILITY PC Resolution (max): 1920x1080 Mac® Resolution (max): 1920x1080 PC Operating System: Windows 10/11 certified; macOS tested Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type C Down Stream: 2 USB 3.2 Type C Down Stream: 1 (15W power charger) USB 3.2 Type C Up Stream: 1 DisplayPort: 1 DisplayPort: 1 DisplayPort: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (polimized): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: Down Stream: 1 (SW Consumption (max): 70W Voltage: AC 100-240V Stand-by: Now Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cobie Organization: Yes Microphone: Ves CONTROLS Physical Controls: (Power) Department Control		
Response Time (Typical GTG): 4ms Response Time (GTG w/OD): 4.19ms Viewing Angles: 178° horizontal, 178° vertical Backlight Life (Hours): 30000 Hrs (Min) Curvature: Flat Refresh Rate (Hz): 120 Variable Refresh Rate Technology: Yes Technology: Yes Color Gamut: RISC: 278' size (Typ) SRGB: 104% size (Typ) RRGB: 104% size (Typ) Pixel Size: 0.311 mm (H) x 0.311 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) COMPATIBILITY PC Resolution (max): 1920x1080 Mac® Resolution (max): 1920x1080 Mac® Resolution (min): 1920x1080 Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 2 USB 3.2 Type C Up Stream: 1 USB 3.2 Type C Up Stream: 2 Up Stream In Type		
Response Time (GTG w/OD):		
Viewing Angles: 178° horizontal, 178° vertical		
Backlight Life (Hours): 30000 Hrs (Min)		
Curvature: Flat		
Refresh Rate (Hz): 120 Variable Refresh Rate Technology: Ves Low Blue Light: Hardware solution Flicker-Free: Yes Color Gamut: STCS: 72% size (Typ) stGE: 100 size (Typ) size (Typ) stGE: 100 size (Typ)		
Variable Refresh Rate Technology:		
Technology: Low Blue Light: Hardware solution Filoker-Free: Yes Color Gamut: NTSC: 72% size (Typ) sRGB: 104% size (Typ) Pixel Size: 0.311 mm (H) x 0.311 mm (V) Surface Treatment: Anti-Glare, Hard Coating (3H) COMPATIBILITY PC Resolution (max): 1920x1080 Mac® Resolution (max): 1920x1080 Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Type C Down stream: 2 (15W power charger) USB 3.2 Ty		120
Flicker-Free: Yes		Yes
NTSC: 72% size (Typ)	Low Blue Light:	Hardware solution
SRCB: 104% size (Typ)	Flicker-Free:	Yes
Section	Color Gamut:	NTSC: 72% size (Typ)
Surface Treatment: COMPATIBILITY PC Resolution (max): 1920x1080 Mac® Resolution (max): 1920x1080 Mac® Resolution (min): 1920x1080 PC Operating System: Windows 10/11 certified; macOS tested Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power power charger) USB 3.2 Type C Up Stream; 1 (15W power charger) USB 3.2 Typ		
### COMPATIBILITY PC Resolution (max): 1920x1080 ### Mac® Resolution (max): 1920x1080 ### Windows 10/11 certified; macOS tested ### Windows 10/11 certi		
PC Resolution (max): 1920x1080 Mac® Resolution (max): 1920x1080 PC Operating System: Windows 10/11 certified; macOS tested Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream; DisplayPort Alt mode: 1 3.5mm Audio Out: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 18W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes CONTROLS Physical Controls: (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Horizontal: 48 ~ 120Hz VIDEO INPUT TMDS: HDM (44 A) PCIE Picelou/Pot 44 (4 3) Microphone Prequency Horizontal: 48 ~ 120Hz VIDEO INPUT		Anti-Glare, Hard Coating (3H)
Mac® Resolution (max): 1920x1080		4000 4000
PC Operating System: Windows 10/11 certified; macOS tested Mac® Resolution (min): 1920x1080 CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream: 1 DisplayPort Alt mode : 3 3.5mm Audio Out: 1 HDMI 1.4: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (Optimized): 18W Consumption (typical): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: (key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DEPERATING CONDITIONS Temperature: 32*F to 104*F (0*C to 40*C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Vertical: 48 ~ 120Hz VIDEO INPUT		
Mac® Resolution (min): 1920x1080		
CONNECTOR USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream; 1 ShipsplayPort Alt mode: 1 J. Shim Audio Out: 1 HDMI 1.4: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 18W Consumption (typical): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DEFRATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Vertical: 48 ~ 120Hz VIDEO INPUT		
USB 3.2 Type A Down Stream: 2 USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream; 1 USB 3.2 Type C Up Stream; 1 3.5mm Audio Out: 1 IDISPLAYPORT Alt mode: 1 JeplayPort: 1 DisplayPort: 1 Displ		1920X1080
USB 3.2 Type C Down stream: 1 (15W power charger) USB 3.2 Type C Up Stream: 1 J.Smm Audio Out: 1 HDMI 1.4: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 18W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: (key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: (hput Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu POPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Vertical: 48 ~ 120Hz WINDEO INPUT		2
USB 3.2 Type C Up Stream; DisplayPort Alt mode: 3.5mm Audio Out: HDMI 1.4: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: POWER Eco Mode (Conserve): Eco Mode (Conserve): 14W Eco Mode (optimized): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: Dower Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Con Screen Display: Department Conditions Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: VMDEO INPUT		
HDMI 1.4: 1 DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22) AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 18W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	USB 3.2 Type C Up Stream;	
DisplayPort: 1 Power in: 3-pin Socket (IEC C14 / CEE22)	3.5mm Audio Out:	1
Power in: AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: On Screen Display: DEFRATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: VAME TABS: HDMI (v1.4) POLE F. DisplayBert (v1.4) Misro TABS: HDMI (v1.4) POLE F.	HDMI 1.4:	1
AUDIO Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	DisplayPort:	1
Internal Speakers: 2Watts x2 POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 22W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Power in:	3-pin Socket (IEC C14 / CEE22)
POWER Eco Mode (Conserve): 14W Eco Mode (optimized): 18W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	AUDIO	
Eco Mode (Conserve):	Internal Speakers:	2Watts x2
Eco Mode (optimized): 18W Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	POWER	
Consumption (typical): 22W Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	Eco Mode (Conserve):	14W
Consumption (max): 70W Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Eco Mode (optimized):	18W
Voltage: AC 100-240V Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	Consumption (typical):	22W
Stand-by: 0.5W Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Consumption (max):	70W
Power Supply: Internal Power Supply ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Voltage:	AC 100-240V
ADDITIONAL HARDWARE Kensington Lock Slot: 1 Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz	Stand-by:	0.5W
Kensington Lock Slot: Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: WIDEO INPUT	Power Supply:	Internal Power Supply
Webcam: 5.0M pixel Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	ADDITIONAL HARDWARE	
Cable Organization: Yes Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: WIDEO INPUT	Kensington Lock Slot:	1
Microphone: Yes CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Webcam:	5.0M pixel
CONTROLS Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu OPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	Cable Organization:	Yes
Physical Controls: Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power) On Screen Display: Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	Microphone:	Yes
Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu DPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	CONTROLS	
Manual Image Adjust, Setup Menu DPERATING CONDITIONS Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz WIDEO INPUT	Physical Controls:	(power)
Temperature: 32°F to 104°F (0°C to 40°C) Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	On Screen Display:	mput Select, Audio/MiC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Humidity (non-condensing): 20% to 90% WALL MOUNT VESA Compatible: 100 x 100 mm INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	OPERATING CONDITIONS	
WALL MOUNT VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT	Temperature:	32°F to 104°F (0°C to 40°C)
VESA Compatible: 100 x 100 mm NPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT TABLE HDM (v1.4) BCLE DisplayBet (v1.3) Misro.		20% to 90%
INPUT SIGNAL Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT TABLE HOM (v1.4) BCLE DisplayBert (v1.3) Misro		100 x 100 mm
Frequency Horizontal: 30 ~ 135KHz Frequency Vertical: 48 ~ 120Hz VIDEO INPUT TABLE HDMI (vd.4) BCLE DisplayBert (vd. 3) Misro	•	
Frequency Vertical: 48 ~ 120Hz VIDEO INPUT TABLE HDMI (vd.4.) PCLE DisplayBert (vd. 2) Misro.		30 ~ 135KHz
VIDEO INPUT		
TMDS HDMI (v4.4) BCLE DisplayPort (v4.2) Migra	•	
	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro-

_	D	c	n	NI	^	R/	41	r

Height Adjust (mm):	150
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°
Pivot (Right/Left):	90° / 90°

5.3

WEIGHT (IMPERIAL)

 Net (lbs):
 11.7

 Net Without Stand (lbs):
 8.2

 Gross (lbs):
 17.9

WEIGHT (METRIC) Net (kg):

Net Without Stand (kg): 3.7
Gross (kg): 8.1

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.): 27.6 x 20.7 x 4.9

Physical (in.): 24.09 x 15.74-21.65 x 8.11

Physical Without Stand (in.): 24.09 x 15.25 x 2.33

DIMENSIONS (METRIC) (WXHXD)

 Packaging (mm):
 700 x 525 x 125

 Physical (mm):
 611.8 x 399.9~549.9 x 206.1

 Physical Without Stand (mm):
 611.8 x 387.3 x 59.2

GENERAL

Regulations: cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy

VG2741V x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI
Cable (v1.4; Male-Male) x1, USB Type-C Cable (MaleMale; with Type-A adapter) x1, Quick Start Guide x1

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: "Warranty offered may differ from market to market

Power Management: Energy Star standards, EPEAT

