

VG2752-2K - 27" 1440P IPS ERGONOMIC MONITOR I 65W USB-C

Key Features

- Single-cable USB-C connectivity delivers video, audio, data and 65W charging
- 2K resolution provides greater clarity and more screen space
- Enhanced comfort with an ergonomic design and faster setup with a quick deploy stand
- Versatile connectivity options including HDMI and DisplayPort inputs
- Integrated USB hub with x2 USB-C ports (15W) and x2 USB-A ports
- Reduced carbon footprint with 100% recyclable, FSC-certified packaging
- Pair with a ViewSonic VG58 monitor to build the ultimate workstation







PANEL



RESOLUTION



Product **Description**

Transform your workspace with the ViewSonic® 27" VG2752-2K monitor. This 27" high-performance monitor offers stunning 2K resolution and SuperClear® IPS panel technology for vibrant, true-to-life colors. With USB-C connectivity, users can easily streamline their setup and cut out the cable clutter as they enjoy 65W of charging, data, audio, video, and power over a single cable. An HDMI port, DisplayPort, and an integrated USB hub (x2 USB-C ports, x2 USB-A ports) make it easy to connect your favorite devices. Designed for all-day comfort, this monitor features an ergonomic stand that allows for height, pivot, swivel, and tilt adjustments, while a 35-degree tilt makes it ideal for use with standing desks and team discussions. Effortlessly expand your workspace with a thin-bezel design and USB-C daisy-chaining, allowing for a streamlined, multi-monitor setup built to help you achieve greater productivity and efficiency. Sustainability meets convenience with biodegradable packaging, a quick-deploy stand, integrated cable management, and a built-in client mount for a faster, cleaner installation.

Specifications

More Information	
UPC	766907031768
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,500:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	350 cd/m2
Color Space Support	8 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	2560x1440 @ 100Hz
Mac® Resolution (max)	2560x1440 @ 100Hz
USB Type A	2
USB Type C	x1 (Upstream, v3.2 Gen2, DP Alt mode, 65W); x2 (Downstream, v3.2 Gen2, 15W)
HDMI 2.0 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	109W
Eco Mode (optimized)	115W
Consumption (typical)	120W
Consumption (max)	200W
Voltage	100-240 VAC
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1

Physical Controls Joystick key: Up, Right, Down, Left, Center; Power On Screen Display Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu 32-104º F (0 - 40º C) **Temperature Humidity (non-condensing)** 20-90% **VESA Compatible** 100 x 100 mm **Height Adjust** 150 mm / 5.9 in Swivel 90º Pivot (Right/Left) 90º / 90º Tilt (Forward/Back) 5º / 30º cTUVus, FCC0B, ICES003, Energy Star 8.0, EPEAT Silver, CEC Regulations Net (lbs) 16.4 Net Without Stand (lbs) 11.0 Gross (lbs) 22.4 7.4 Net (kg) Net Without Stand (kg) 5.0 10.2 Gross (kg) 27.6 x 16.7 x 6.5 Packaging (in.) 24.12 x 15.84~20.69 x 8.6 Physical (in.) Physical Without Stand (in.) 24.12 x 14.6 x 1.76 702.0 x 425.0 x 166.0 Packaging (mm) 612.6 x 402.32~526.64 x 218.47 Physical (mm) Physical Without Stand (mm) 612.6 x 359.77 x 44.75 VG2752-2K, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, USB Type-C Gen2 Cable **Package Contents** (Male-Male; with Type-A adapter) x1, Quick Start Guide x1 Recycle/Disposal Please dispose of in accordance with local, state or federal laws. Warranty Three-year limited warranty on parts, labor and backlight

UPC: 766907031768







Contact Sales
ViewSonic.com

888.881.8781
email:
salesinfo@viewsonic.com