



VG2756A-2K - 27" 1440P ERGONOMIC IPS DOCKING MONITOR WITH 100W USB C, RJ45 AND DAISY CHAIN

Key Features


- 27 Inch QHD (2560x1440p) IPS monitor with thin bezels and 60Hz refresh rate
- Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 100W charging over one cable
- Advanced ergonomics (40-degree tilt, swivel, rotate and height) for all-day comfort
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Easy-to-install quick release stand with carrying handle and client mount
- The VG2456a-2K supports PC, Mac and more with USB-C, RJ45, HDMI, DisplayPort In & Out (Daisy Chain), USB



27
DISPLAY



IPS
PANEL



2560 X 1440
RESOLUTION



Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756a-2K is a 27" QHD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the USB Type-C connectivity allows easy single-cable connectivity to provide data, audio, video and up to 100w power delivery. DisplayPort out allows easy Daisy Chain capability for a dual monitor set-up for additional screen real estate. That's not all, the integrated USB hub allows easy connectivity for your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

Specifications

	More Information
UPC	766907021691
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 X 1440
Mac® Resolution (max)	2560 X 1440
USB Type A	2
USB Type B	1
USB Type C	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	20.8W
Eco Mode (optimized)	25.1W
Consumption (typical)	30.7W
Consumption (max)	74W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W

Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v1.4): 15 ~ 90 KHz, DisplayPort: 15 ~ 90 KHz, USB-C: 15 ~ 90 KHz
Frequency Vertical	HDMI (v1.4): 49 ~ 75 Hz, DisplayPort: 49 ~ 75 Hz, USB-C: 49 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 40°
Net (lbs)	16.7
Net Without Stand (lbs)	11.6
Gross (lbs)	23.5
Net (kg)	7.6
Net Without Stand (kg)	5.3
Gross (kg)	10.7
Packaging (in.)	27.2 x 16.9 x 8.6
Physical (in.)	24.1 x 15.99~20.99 x 8.0
Physical Without Stand (in.)	24.1 x 14.2 x 2.0
Packaging (mm)	692 x 430 x 218
Physical (mm)	612 x 406.19~533.24 x 202
Physical Without Stand (mm)	612 x 362 x 52
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
Package Contents	VG2756a-2K Display, Power Cable, DP to DP Cable, USB Type C cable, USB A/B Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907021691



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com