

## Key **Features**

- Apple Compatible: MAC Ready with 90W USB-C connectivity plus 95% DCI-P3 International Digital Film Standard color gamut
- Hollywood Color: VESA verified HDR400 with Nano IPS meets big screen standards for Cinematic quality.
- Great for B-Roll: 165 Hz Refresh Rate ideal for stellar sequences
- Instant Color Adjustment: Our exclusive ColorPro Wheel puts color calibration and adjustments at your fingertips with Adobe Software and on-screen displays
- Portable Darkroom: Foldaway hood attaches instantly to eliminate ambient light when you need to "go dark"



## Product **Description**

Introducing the world's first professional monitor with an integrated color calibrator plus Nano IPS Color Gamut, 95% DCI-P3 capability & 165Hz refresh rate. Outstanding visual performance and unmatched color capability combine with award-winning ergonomic design and fingertip controls in our ColorPro VP76 Series Professional Monitors from ViewSonic. Designed exclusively to meet the visual needs of world-class photographers, vloggers, video editors, animators and game designers, ColorPro stands apart through a marriage of the latest tech and human touch. With integrated access to Adobe and Capture One editing software, ColorPro was created to surpass your expectations through a combination of elegant design, outstanding technology and a simple, intuitive interface for easy color adjustment.

Visit Us

www.viewsonic.com

DISPLAY		ADDITIONAL HARDWARE	
Display Size (in.):	27	Kensington Lock Slot:	1
Viewable Area (in.):	27	Cable Organization:	Yes
Panel Type:	IPS Technology	CONTROLS	
Resolution:	2560 x 1440	Physical Controls:	Joystick key: Up, Right, Down, Left,
Resolution Type:	QHD (Quad HD)		Center; Power
Static Contrast Ratio:	1,000:1 (typ)	On Screen Display:	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu
Dynamic Contrast Ratio:	20M:1	OPERATING CONDITIONS	
Light Source:	LED	Temperature:	32°F to 104°F (0°C to 40°C)
Brightness:	400 cd/m² (typ)	Humidity (non-condensing):	20% to 90%
Colors:	1.07B	WALL MOUNT	
Color Space Support:	10 bit (8 bit + A-FRC)	VESA Compatible:	100 x 100 mm
Aspect Ratio:	16:9	INPUT SIGNAL	
Response Time (Typical GTG):	3ms		HDMI (v2.0): 20 ~ 230KHz,
Response Time (GTG w/OD):	3ms	Frequency Horizontal:	DisplayPort (v1.4): 30 ~ 250KHz, Type C: 30 ~ 250KHz
Response Time (MPRT):	1ms		HDMI (v2.0): 48 ~ 144Hz, DisplayPor (v1.4): 48 ~ 165Hz, Type C: 48 ~ 165Hz
Viewing Angles:	178° horizontal, 178° vertical	Frequency Vertical:	
		VIDEO INPUT	
Backlight Life (Hours):	30000 Hrs (Min)		TMDS - HDMI (v2.0), PCI-E -
Curvature:	Flat	Digital Sync:	DisplayPort (v1.4), Micro-Packet - Type C
Refresh Rate (Hz):	165	ERGONOMICS	.,,
Variable Refresh Rate Technology:	Yes	Height Adjust (mm):	120
Blue Light Filter:	Yes	Swivel:	120°
Flicker-Free:	Yes	Tilt (Forward/Back):	-3° / 21°
Color Gamut:	Adobe RGB: 99% size / 87% coverage (Typ) DCI-P3: 98% size / 95% coverage (Typ) EBU: 131% size	Pivot (Right/Left):	90° / 90°
		WEIGHT (IMPERIAL)	30 7 30
	/ 100% coverage (Typ) REC709:	Net (lbs):	18.5
	133% size / 100% coverage (Typ) SMPTE-C: 144% size / 100% coverage (Typ) NTSC: 94% size (Typ) sRGB: 133% size / 100% coverage	Net Without Stand (lbs):	11.2
		Gross (lbs):	28.2
	(Тур)	WEIGHT (METRIC)	20.2
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	Net (kg):	8.4
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Net Without Stand (kg):	5.1
COMPATIBILITY		Gross (kg):	12.8
PC Resolution (max):	2560x1440	DIMENSIONS (IMPERIAL) (W	
Mac® Resolution (max):	2560x1440	Packaging (in.):	27.2 x 19.9 x 8.9
PC Operating System:	Windows 10/11 certified; macOS tested	Physical (in.):	24.2 x 17.69~22.42 x 9.2
Mac® Resolution (min):	2560x1440		24.2 x 17.09~22.42 x 9.2 24.2 x 14.3 x 2.1
CONNECTOR		Physical Without Stand (in.):  DIMENSIONS (METRIC) (WXI	
USB 3.1 Type C - Downstream:	1	Packaging (mm):	•
USB 3.2 Type A Down Stream:	2		692 x 505 x 225
USB 3.2 Type B Up Stream:	1	Physical (mm):	614 x 449.36~569.36 x 234
USB 3.2 Type C Up Stream;		Physical Without Stand (mm):	614 x 364 x 54
DisplayPort Alt mode :	1 (90W power charger)	GENERAL	TIN 500 B 1050000 5
Micro USB:	1		cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, CE, CE EMC, CB
3.5mm Audio Out:	1	Regulations:	RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, CCC,
HDMI 2.0 (with HDCP 2.2):	2		China RoHS, China Energy Label, CECP
DisplayPort:	1		VP2776 x1, 3-pin Plug (IEC C13 /
Power in:	3-pin Socket (IEC C14 / CEE22)	PACKAGE CONTENTS:	CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, Quick Start Guide x1
AUDIO			
Internal Speakers:	3Watts x2		Hood x1, ColorPro Wheel x1
POWER		Recycle/Disposal:	Please dispose of in accordance with
Eco Mode (Conserve):	33.4W		local, state or federal laws.
Eco Mode (optimized):	36.3W	Warranty:	*Warranty offered may differ from market to market
Consumption (typical):	39.5W	Power Management:	Energy Star standards, EPEAT
Consumption (max):	43.5W	,	
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.