

#### VP3256-4K - 32" COLORPRO™ 4K UHD IPS MONITOR WITH 60W USB C, SRGB, HDR10 AND PANTONE VALIDATED

#### **Key Features**

- 32 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels, HDR10 and 60Hz refresh
- In addition to fast data, audio and video transfer, USB-C also provides quick 60W charging over a single cable
- Advanced ergonomics (tilt, swivel, pivot and height) for all-day comfort
- · Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, Rec. 709, and DICOM-SIM color spaces and Delta E<2 accuracy
- This monitor has been certified as capable of reproducing Pantone Matching System colors
- · Adaptive Sync technology enables smooth frame rates to aid you in battle
- The VP3256-4K supports laptops, PCs, Macs and more with USB-C, HDMI, USB and DisplayPort inputs





**DISPLAY** 





3840 x 2160 **PANEL RESOLUTION** 



## Product **Description**

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP3256-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel for 100% sRGB and a sleek 3-sided frameless design, the VP3256-4K provides a near-seamless viewing experience. The VP3256-4K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your customers will see, as well.

### **Specifications**

UPC	766907014532
Screen Size	32
Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	32W
Eco Mode (optimized)	39W
Eco Mode (optimized)  Consumption (typical)	39W 46W
Consumption (typical)	46W
Consumption (typical)  Consumption (max)	46W 125W
Consumption (typical)  Consumption (max)  Voltage	46W 125W 100-240 VAC
Consumption (typical)  Consumption (max)  Voltage  Stand-by	46W 125W 100-240 VAC 0.5W
Consumption (typical)  Consumption (max)  Voltage  Stand-by  Power Supply	46W 125W 100-240 VAC 0.5W Internal
Consumption (typical)  Consumption (max)  Voltage  Stand-by  Power Supply  Cable Organization	46W 125W 100-240 VAC 0.5W Internal

Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	TMDS, PCI-E, Micro-Packet: 15 ~ 136 KHz
Frequency Vertical	TMDS, PCI-E, Micro-Packet: 24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	1209
Pivot (Right/Left)	90º / 90º
Net (lbs)	24.0
Net Without Stand (lbs)	15.8
Gross (lbs)	33.7
Net (kg)	10.9
Net Without Stand (kg)	7.2
Gross (kg)	15.3
Packaging (in.)	33.1 x 20.5 x 12.8
Physical (in.)	28.2 x 20.2~25.4 x 10.4
Physical Without Stand (in.)	28.2 x 16.7 x 2.6
Packaging (mm)	840.0 x 520.0 x 326.0
Physical (mm)	715.0 x 514.0~644.0 x 265.0
Physical Without Stand (mm)	715.0 x 423.0 x 66.0
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Package Contents	VP3256-4K, Power Cable, USB-C Cable, HDMI cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907014532







# Contact Sales ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com