

27" Full HD Ultra-Slim Monitor

Frameless Design and SuperClear® IPS Panel Technology

VX2776-smhd



Available for this model:
**Privacy Filter
Screen Protector**
VSPF2700
(Sold Separately)

Style and substance go hand-in-hand with the ViewSonic® VX2776-smhd 27" Full HD monitor. SuperClear® IPS panel technology, wide viewing angles, and best-in-class screen performance deliver outstanding visual clarity great for vibrant entertainment and gaming. A premium ID includes an ultra-slim profile, unique desktop stand, and a sleek edge-to-edge frameless screen, that when combined with vivid 1920x1080 resolution and dual speakers, deliver an immersive viewing experience for home entertainment and multimedia applications. Versatile HDMI, DisplayPort, and VGA inputs keep you connected to your favorite devices, while the modern, flush-mount frameless bezel design makes a standout statement in any home.

Key Features:

Ultra-slim panel with frameless design

SuperClear IPS panel technology

Versatile connectivity

Full HD 1080p resolution

Superior color rendering and intuitive settings

Designed for:


Home

27" Full HD Ultra-Slim Monitor

VX2776-smhd



Menu Controls



AC In
Kensington® Lock Slot
Headphones
Audio In
VGA
HDMI
DisplayPort

Specifications

LCD PANEL	Type	IPS Type, a-si TFT Active Matrix LCD
	Display Area	23.5" horizontal x 13.2" vertical; 27.0" diagonal
	Optimum Resolution	1920x1080
	Brightness	250 cd/m ² (typ.)
	Contrast Ratio	1000:1 (typ.)
	Dynamic Contrast Ratio	80M:1
	Viewing Angles	178° horizontal, 178° vertical
	Colors	16.7M (6bit + A-FRC)
	Response Time	7ms (GTG)
	Backlight	White-light LED
	Backlight Life	30,000 hours (min.)
	Panel Surface	Anti-glare, hard-coating (3H)
VIDEO INPUT	Digital	DisplayPort, HDMI
	Analog	VGA
	Frequency	Fh: 24~82kHz, Fv: 50~75Hz
	Sync	Separate Sync, Composite Sync, Sync on Green, TMDS, PCI-E
AUDIO OUTPUT	Speakers	3-watt (x2)
COMPATIBILITY	PC	Up to 1920x1080 non-interlaced
	Mac®	Up to 1920x1080
CONNECTOR	Video In	DisplayPort, HDMI, VGA
	Audio In	3.5mm mini jack
	Headphones	3.5mm mini jack
	Power	External Power Adapter
CONTROLS	Front Panel Buttons	GameMode, 1, 2, 3, 4, Power
	OSD	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

ERGONOMICS	Tilt	Forward 5° / Back 17°
POWER	Voltage	AC 100~240V (universal), 50 / 60Hz
	Consumption	24W (typ.) / 32W (max.)
	Optimize	20W (typ.)
	Conserve	17W (typ.)
OPERATING CONDITIONS	Temperature	32~104° F (0~40° C)
	Humidity	20~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with Stand	24.5 x 18.2 x 8.2 in. / 621 x 462.6 x 209 mm
	Packaging	27.0 x 17.7 x 4.5 in. / 685 x 450 x 115 mm
WEIGHT	Net with Stand	8.2 lb. / 3.7 kg
	Gross	12.1 lb. / 6.6 kg
REGULATIONS		CE EMC, CB, RoHS BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, EEL, cULus, FCC-B, DOE ENERGY STAR 6.0, DOE EPEAT (Silver), NRCan, UL-MX-CoC, Mexico Energy
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		Three-year limited warranty on parts, labor and backlight

Optional Accessories

HDMI to DVI cable 6FT	CB-00008948
Mini DisplayPort to DisplayPort cable 6FT	CB-00010958
DisplayPort to DisplayPort cable 30FT	CB-00010684
DisplayPort Male to VGA Female Adapter (Single Link).....	CB-00011486
DisplayPort to DisplayPort cable 6FT	CB-00010555
DisplayPort to DVI Adapter.....	LCD-CABLE-001

What's in the box?

VX2776-smhd monitor, Power cable, AC/DC adapter, Audio cable, VGA cable, HDMI cable, Quick Start Guide, ViewSonic Wizard CD



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.