

NovoTouch

NovoTouch EK755i

True 75" 4K interactive display with wireless collaboration and touch interaction for the classroom



Features

- 75" display with ultraHD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- Backlit D-LED (IPS panel) technology for brighter pictures, flawless colors, richer textures, and extra wide viewing angels (178°/178°)
- Preconfigured with NovoConnect wireless presentation and collaborative system for cable-free and hassle-free presenting in the classroom
- Connect up to 64 users simultaneously, and allow 4 people to present on one display to facilitate large group work
- Optional LauncherPlus wireless dongle connects to any visitor's laptop for a direct plug-n-play WiFi connection without impacting an existing network
- High contrast ratio and fast response time deliverables crisp, readable content
- Interactive functionality with up to a 20-point finger touch capabilities (10-point writing, 20-point touch) for on-screen annotation, drawing and common gesture controls
- Simple wireless display and true fast collaboration solution thanks to WiFi 6, 802.11AX dual-band 2.4/5GHz support
- Provide API or Remote Manager with IT management software with automatic discovery and configuration
- Full suite of connectivity ports including HDMI-In VGA-In, Audio-In/Out, LAN, RS232 and USB.
- Front bezel USB 3.0 ports for quick connection to USB memory drives and data
- 4mm thick toughened glass for added protection against scratches or screen damage
- Support HDMI-IN on presentation or digital signage mode
- Built-in NovoDS capability as an all-in-one digital signage solution, easy to set up and manage via Windows/Mac software or NovoDS.com Cloud service
- Daily auto-reboot and low blue light support
- VESA compliant mounting for easy installation
- Powerful front- facing stereo audio speakers with up to 32W of total power (16Wx2) and multiple audioin/out ports

Display	Type/Technology		Backlit D-LED (IPS Panel)
	Panel Size		75"
	Brightness (Typ)		350cd/m2
	Contrast Ratio (Typ)		4,000:1
	Native Resolution		4K Ultra-HD (3840 x 2160)
	Viewing Angle (H/V)		178°/178°
	Aspect Ratio		16:9
	Response Time (MS)		8.5ms (Typ)
	Refresh Rate (Hz)		60Hz
	Estimated Life Time (Typ)		30,000 hours (Min)
	Display Color (Bit) Installation Orientation		1.07 billion (10-bit)
			Landscape
	Daily Operation (Hours/Days) Technology		16/7 Infrared Touch
Interactivity	Touch	Writing	10 Point (Standard)
	Points	Touch	20 Point (Standard)
	Accuracy	Finger	±1.0mm (Over 90% area)
		Passive Pen	±1.0mm (Over 90% area)
	Response T		< 10ms
	Touch Resolution		32,768 x 32,768
			4mm Thick Toughened Glass (Level 7H on
	Surface Protection		Mohs Scale of Mineral Hardness)
	Touch Tools		Finger, Stylus, Glove, Opaque Objects
	System Version		Android™ v9.0 (upgrade to v11.0)
	CPU		Multi-Core High-Performance ARM®CPU
Operating System	GPU		4*Mali™ G52
	RAM		8GB DDR3
	Internal Storage		64GB (eMMC Flash)
	Output	5	HDMI v2.0 (x3) (HDCP v2.2 Compliant)
		Display	USB Type C (x1)
		Audio	VGA-In (x1) Audio-In (3.5mm) (x1)
		Display	HDMI-Out v1.4(x1)-1080P@60Hz (option)
		Display	Audio-Out (3.5mm) (x1)
		Audio	SPDIF-Out (x1)
	Internet		LAN (RJ45, 10/100/1000M) (x2)
	Control		
	Control		RS232-ln (x1)
Connectivity	Control	Wifi	RS232-ln (x1) WiFi 6, IEEE 802.11 a/b/g/n/ac/ax
Connectivity		Wifi (USB Module)	
Connectivity	Control	Wifi (USB Module)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax
Connectivity		Bluetooth I/R Receiver	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance)
Connectivity		Bluetooth	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2)
Connectivity		Bluetooth I/R Receiver	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1)
Connectivity		Bluetooth I/R Receiver	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input
Connectivity	Wireless	Bluetooth I/R Receiver Front	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) Support up to 65W / display input USB 3.0 (x2)
Connectivity	Wireless	Bluetooth I/R Receiver Front	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input
Connectivity	Wireless	Bluetooth I/R Receiver Front Side Bottom	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port)
Connectivity	Wireless	Bluetooth I/R Receiver Front Side Bottom	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1)
·	Wireless USB Window Moo	Bluetooth I/R Receiver Front Side Bottom dule (Option)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option)
·	Wireless USB Window Mod Speakers Power Supp Consumption	Bluetooth I/R Receiver Front Side Bottom dule (Option)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W
Audio	Wireless USB Window Mod Speakers Power Supp Consumption Standby Model	Bluetooth I/R Receiver Front Side Bottom dule (Option) Sily (Internal)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby)
Audio Power	Wireless USB Window Mod Speakers Power Supp Consumption Standby Mod Dimension (to the standby	Bluetooth I/R Receiver Front Side Bottom dule (Option) Sily (Internal)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm
Audio Power Physical	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (In Weight	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx Hx D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg
Audio Power	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension () Weight VESA Mount	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx Hx D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm
Audio Power Physical Characteristics	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (Weight VESA Mound Color	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx Hx D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey
Audio Power Physical	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension () Weight VESA Mount	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx Hx D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor
Audio Power Physical Characteristics	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (Weight VESA Mound Color	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB
Audio Power Physical Characteristics	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (Weight VESA Mound Color	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor
Audio Power Physical Characteristics	Wireless USB Window Models Speakers Power Supplest Consumption Standby Models Dimension (In Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, HDMI Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall
Audio Power Physical Characteristics Sensor	Wireless USB Window Models Speakers Power Supplest Consumption Standby Models Dimension (In Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) ➤ Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, HDMI Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall Mount Kit
Audio Power Physical Characteristics	Wireless USB Window Models Speakers Power Supplest Consumption Standby Models Dimension (In Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, HDMI Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall Mount Kit * Sensor Box (including Air Quality/
Audio Power Physical Characteristics Sensor	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, Holl Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall Mount Kit * Sensor Box (including Air Quality/ Temperature Detector, Motion Sensor,
Audio Power Physical Characteristics Sensor	Wireless USB Window Models Speakers Power Supplest Consumption Standby Models Dimension (In Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, HDMI Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall Mount Kit * Sensor Box (including Air Quality/ Temperature Detector, Motion Sensor, NFC Reader, Proximity Sensor)
Audio Power Physical Characteristics Sensor	Wireless USB Window Mode Speakers Power Supp Consumption Standby Mode Dimension (Weight VESA Mound Color Built-in	Bluetooth I/R Receiver Front Side Bottom dule (Option) bly (Internal) in de Lx H x D)	WiFi 6, IEEE 802.11 a/b/g/n/ac/ax (2.4GHz/5GHz) BT 5.0 Front (x1) (±25° Angle, >8m Distance) USB 3.0 (x2) USB Type C (x1) > Support up to 65W / display input USB 3.0 (x2) USB Type B (x2) (For Touch Port) USB 2.0 (x1) Slot 1: Standard Intel 80pin OPS (Option) 16W (x2) (Stereo) AC 100 - 240V, 50/60Hz (5.0A) 500W <0.5W (Standby) 1,709 x 1,020 x 86mm 51.3kg 6 - M8 × 25mm, 800 x 400mm Grey Lighting Sensor AC Power Cord (3m), WiFi 6 USB Module, Holl Cable, Touch USB Cable, Audio Cable, Stylus (x2), Remote Control (W/Batteries), Documentation Kit, Wall Mount Kit * Sensor Box (including Air Quality/ Temperature Detector, Motion Sensor,

©2022 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.