

NovoConnect

NovoConnect NC-X900

NC-X900 is the flagship model of Vivitek's latest NovoConnect series, which provides cost-effective and hassle-free solutions for easy collaboration and engaging meetings

Features

- Wireless presentation from laptops, tablets, and phones, with built-in support of AirPlay[®], Google Cast[™] and Miracast[®] for Windows 10
- Connect up to 64 users; display up to four windows simultaneously on one screen
- On-screen annotation and remote annotation (AirNote)
- AES-256 encryption to safe guard data security
- Network-based remote management and maintenance software for ease of deployment
- 4K display output
- One HDMI input to facilitate easy integration with other video sources
- Supports LauncherPlus (WQL400) external wireless dongle (Optional accessory)
- PoE (Power over Ethernet) for easy deployment

Photos



Specifications

opcomoand				
Model Number		NovoConnect NC-X900		
Product Compatibility		Projectors or displays with HDMI input		
CPU Processor		Multi-Core High-Performance ARM [®] CPU		
Display Resolutions		720p (1280 x 720)@50/60Hz, 1080p (1920 x 1080)@ 50/60Hz,, UHD-4K (3840 x 2160)@ 30/50/60Hz,		
Output Orientation		Landscape		
Memory/Storage Expansion		RAM		DDR3 4GB
		Internal Storag	ge	16GB (eMMC Flash)
		External		microSD Card Slot (Up to 32GB), USB Type A & C Flash Drive (Up to 32GB)
Connectivity	Input	USB2.0 Type A (x1), USB Type C (x1), HDMI-In v1.4, microSD Slot, Line-In (3.5mm), RS-232 (3.5mm), RJ45 (PoE PD), Power Input (5V/3A)		
	Output	HDMI-Out v2.0 (HDCP v2.2 Compliant), Audio-Out (3.5mm)		
	Internet (Ethernet)	RJ45 (x1) (10/100/1000 Mbps (Compatible PoE Powered Device))		
	Wireless	Wifi		2 x 802.11 ac/b/g/n (2.4GHz & 5GHz Frequency Bands), 2T2R))
		Bluetooth		V4.1
Wifi Sharing Modes		Hotspot Mode		Up to 8 participants
		Client Mode		Up to 64 participants
		Miracast®		1 participant for Miracast [®] , up to 63 participants via network
LED Indicator		Green (System Power On), Blue (Network Activity), Red (System Stand By)		
Button		Reset		
Screen Mirroring (Multi-Platform OS Application Support)		Windows [®] , Mac [®] , Android [™] , iOS, Chrome (Book)		
Accessories		Standard AC Power Adapter (Depends on Region), USB Power Cable, HDMI Cable, F Remote Control, Mounting Kit		
		Optional LauncherPlus (WQL400)		
Power Supply/Consumption (AC Adapter)		100 ~ 240 V AC, 50/60Hz, DC Output: 5V/3A, 15W		
Available Color		Black		
Security Solutions		AES-256 Encryption, Kensington [®] Security Slot		
Weight		446g (15.7oz)		
Dimensions (L x W x H)		196mm x 140mm x 28.9mm (7.7' x 5.5' x 1.1')		

©2020 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice. Images are for reference only.



