



Wiremold  
**Outdoor Ground Box 30A, 250V TURNLOK®, Locking Receptacle L6-30R, Brown**  
Part No. XB814CL630BN



The brown Outdoor Ground Box cover assembly is prewired with (1) 30A L6-30R 240V corrosion-resistant duplex receptacles. CAUTION: All ground box electrical circuits must be protected by a Ground Fault Circuit Interrupter upstream from the ground box. NOTE: Cover must be closed while in use. Use only molded plug and cord assemblies that are rated for outdoor use. NOTE: Maximum length of plug allowed at end of cord is 3" (76mm).

## Features & Benefits

cUL Coming Soon UL listed to UL50E Type 6P (NEMA 6P) and IP68 requirements while in use ADA compliant Outdoor-rated construction Keeps receptacles and connections dry even when submerged

## Specifications

### General Info

Product Line	Wiremold	UPC Number	786776187250
Country Of Origin	China	Construction	Assembled
Number of Knockouts	1	Application Sector	Commercial
Standard	UL Listed Outdoor In-Ground Boxes: File E486738 Guide QCNL.	Type	Ground Box

### Listing Agencies / 3rd Party Agencies

cULus ListingNumber	E486738	cULus Listed	Yes
---------------------	---------	--------------	-----

### Additional Information

RoHS Conformant	Yes
-----------------	-----

### Technical Information

Number of Outlets	1
-------------------	---